

View Online at https://aerobasegroup.com/nsn/4210-01-306-6809

| Maximum Operating Pressure: 150.0 pounds per square inch Body Style: Straight thu Media For Which Designed: Air or water, fresh First End Connection Type: Plain face flange First End Style Designator: Plain First End Style Designator: Plain First End Style Designator: Plain First End Flange Shape Style: Round First End Bolt Hole Quantity: 8 Second End Relationship With First End: Identical Second Ford Relationship With First End: Identical Secon | | | | |
|--|-----------------------------|-----------------|--|--|
| Body Style: Straight thru Media For Which Designed: Air or water, fresh First End Connection Type: Plain face flange First End Style Designator: Plain First End Shape Style: Round First End Flange Shape Style: Round First End Bolt Hole Quantity: 8 Second End Relationship With First End: Identical Second End Relationship With First End: Identical: Path End Style Designatica: First End Connection Quantity: 2 Bonted Attachment Method: Ident | Maximum Operating Press | ure: | | |
| Straight thu Media For Which Designed: Air or water, fresh First End Connection Type: Plain dase flange First End Silve Designator: Plain First End Flange Shape Style: Round First End Bolt Hole Quantity: 8 Second End Relationship With First End: Identical State Material: State Control Device: Disk, lift Valve Operation Method: Automate End Connection Quantity: 2 Bonted Attachment Method: Bolted Sprinkler System For Which Designed: Na Na Dirit Of Measure | 150.0 pounds per square inc | h | | |
| Air or water, fresh First End Connection Type: Plain face flange First End Style Designator: Plain Plain face flange First End Style Designator: Plain First End Style Designator: Plain First End Style Designator: Plain Fort End Style Designator: Round First End Style Designator: Round Second End Relationship With First End: Identical Second End Relationship With First End: Identical Steel, corrosion resisting Flow Control Device: Disk, lift Valve Operation Method: Automatic Lutomatic Botted Sprinkler System For Which Designed: Dip pipe Shell file: Val Init of Measure: Comone: Como | Body Style: | | | |
| Air or water, fresh First End Connection Type: Plain face flange First End Style Designator: Plain First End Style Designator: Plain First End Flange Shape Style: Round First End Bolt Hole Quantity: 8 Second End Relationship With First End: Identical Set Material: Steel, corrosion resisting Flow Control Device: Disk, lift Valve Operation Method: Automatic End Connection Quantity: 2 Bointet Attachment Method: Automatic End Connection Quantity: 2 Bointet Attachment Method: Automatic Politer Na Shell Inte: Na Chi Measure: - Comment Conserver - Prover Fig: Disk [fig: | Straight thru | | | |
| First End Connection Type: Plain face flange First End Style Designator: Plain Plain First End Style Designator: Plain First End Flange Shape Style: Round First End Bolt Hole Quantity: 8 Second End Relationship With First End: Identical Seat Material: Steel, corrosion resisting Flow Control Device: Disk, lift Valve Operation Method: Automatic End Connection Quantity: 2 Boited Sprinker System For Which Designed: Int Of Measure: ~ Valve Operation: Na Disk lift: Na Distation: Distation: Distation: Platt Life: Na Distation: Na Find: Na Find: Na Find: Na Find: Na Find: Na Statistion: Na Find: Na Statistion: Statistion: <td>Media For Which Designed</td> <th>1:</th> <td></td> <td></td> | Media For Which Designed | 1: | | |
| Plain face flange First End Style Designator: Plain First End Shape Style: Round First End Bolt Hole Quantity: 8 Socon End Relationship With First End: Identical Seat Material: Steel, corrosion resisting Flow Control Device: Disk, lift Automatic End Connection Quantity: 2 Bonnet Attachment Method: Bolted Sprinker System For Which Designed: Diry pipe Sheft Life: Na Unit Of Messure: Panillarization: No Fing: | Air or water, fresh | | | |
| First End Style Designator: Plain First End Flange Shape Style: Round First End Bolt Hole Quantity: 8 Second End Relationship With First End: Identical Set Material: Steel, corrosion resisting Flow Control Device: Disk, lift Valve Operation Method: Automatic End Connection Quantity: 2 Solted Spinkler System For Which Designed: Dy pipe Sheff Life: N/a Uit Of Measure: - - Pomilitarization: No Fig: | First End Connection Type | >: | | |
| Plain First End Flange Shape Style: Round First End Bolt Hole Quantity: 8 Second End Relationship With First End: Identical Set Material: Steel, corrosion resisting Flow Control Device: Disk, lift Vate Operation Method: Roundatio Botted Sorted Ktachment Method: Botted Sprinkler System For Which Designed: Dy pipe Shelf Life: Na Unt Of Measure: - - Pomilarization: No Fig: | Plain face flange | | | |
| First End Flange Shape Style: Round First End Bolt Hole Quantity: 8 Second End Relationship With First End: Identical Seat Material: Steel, corrosion resisting Flow Control Device: Disk, lift Valve Operation Method: Automatic Bonnet Attachment Method: Bolted Sprinkler System For Which Designed: Diy pipe Shelf Life: Na Dit Of Measure: Formiliarization: No Fig: | First End Style Designator | : | | |
| Round First End Bolt Hole Quantity: 8 Second End Relationship With First End: Identical Seat Material: Steel, corrosion resisting Flow Control Device: Disk, lift Valve Operation Method: Automatic End Connection Quantity: 2 Boinet Attachment Method: Bolted Sprinkler System For Which Designed: Dry pipe Sheff Life: Na Unit Of Measure: Poinellarization: No Fig: | Plain | | | |
| First End Bolt Hole Quantity: 8 Second End Relationship With First End: Identical Seat Material: Steel, corrosion resisting Flow Control Device: Disk, lift Valve Operation Method: Automatic End Connection Quantity: 2 Bonnet Attachment Method: Bolted Sprinkler System For Which Designed: Dry pipe Shelf Life: Na Unt Of Measure: mailer Pointilarization: No Fig: | First End Flange Shape St | yle: | | |
| Socond End Relationship With First End: Identical Geat Material: Seat Material: Steel, corrosion resisting Fiow Control Device: Disk, lift Valve Operation Method: Automatic End Connection Quantity: 2 Bonnet Attachment Method: Bolted Bolted Sprinkler System For Which Designed: Dry pipe Shelf Life: Na Unit Of Measure: Demilitarization: No Fig: | Round | | | |
| Second End Relationship With First End: Identical Seat Material: Steel, corrosion resisting Flow Control Device: Disk, lift Valve Operation Method: Automatic End Connection Quantity: 2 Bonnet Attachment Method: Bolted Sprinkler System For Which Designed: Dry pipe Shelf Life: N/a Unit Of Measure: Penilltarization: No Fig: | First End Bolt Hole Quanti | ty: | | |
| Identical Seat Material: Steel, corrosion resisting Flow Control Device: Disk, lift Valve Operation Method: Automatic End Connection Quantity: 2 Bonnet Attachment Method: Bolted Sprinkler System For Which Designed: Dry pipe Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: | 8 | | | |
| Seat Material: Steel, corrosion resisting Flow Control Device: Disk, lift Valve Operation Method: Automatic Automatic End Connection Quantity: 2 Bonnet Attachment Method: Bolted Bolted Sprinkler System For Which Designed: Dry pipe Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: | Second End Relationship | With First End: | | |
| Steel, corrosion resisting Flow Control Device: Disk, lift Valve Operation Method: Automatic End Connection Quantity: 2 Bonnet Attachment Method: Bolted Sprinkler System For Which Designed: Dry pipe Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: | Identical | | | |
| Flow Control Device: Disk, lift Valve Operation Method: Automatic End Connection Quantity: 2 Bonnet Attachment Method: Bolted Sprinkler System For Which Designed: Dry pipe Shelf Life: N/a Unit Of Measure: - Pemilitarization: No Fig: | Seat Material: | | | |
| Disk, lift Valve Operation Method: Automatic End Connection Quantity: 2 Bonnet Attachment Method: Bolted Sprinkler System For Which Designed: Dry pipe Shelf Life: N/a Unit Of Measure: Fomilitarization: No Fig: | Steel, corrosion resisting | | | |
| Valve Operation Method:AutomaticEnd Connection Quantity:2Bonnet Attachment Method:BoltedBoltedSprinkler System For Which Designed:Dry pipeShelf Life:N/aUnit Of Measure:-Demilitarization:NoFig: | Flow Control Device: | | | |
| AutomaticEnd Connection Quantity:2Bonnet Attachment Method:BoltedBorinkler System For Which Designed:Dry pipeShelf Life:N/aUnit Of Measure:Demilitarization:NoFig: | Disk, lift | | | |
| End Connection Quantity: 2 Bonnet Attachment Method: Bolted Sprinkler System For Which Designed: Dry pipe Shelf Life: N/a Unit Of Measure: Demilitarization: No | Valve Operation Method: | | | |
| 2 Bonnet Attachment Method: Bolted Sprinkler System For Which Designed: Dry pipe Shelf Life: N/a Unit Of Measure: Pomilitarization: No | Automatic | | | |
| Bonnet Attachment Method:BoltedSprinkler System For Which Designed:Dry pipeShelf Life:N/aUnit Of Measure:Demilitarization:NoFig: | End Connection Quantity: | | | |
| Bolted Sprinkler System For Which Designed: Dry pipe Shelf Life: N/a Unit Of Measure: Demilitarization: No | 2 | | | |
| Sprinkler System For Which Designed: Dry pipe Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: | Bonnet Attachment Metho | d: | | |
| Dry pipe Shelf Life: N/a Unit Of Measure: Demilitarization: No | Bolted | | | |
| Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: | Sprinkler System For Whic | h Designed: | | |
| N/a Unit Of Measure: Demilitarization: No Fiig: | Dry pipe | | | |
| Unit Of Measure: Demilitarization: No Fiig: | Shelf Life: | | | |
| Demilitarization: No Fiig: | N/a | | | |
| Demilitarization: No Fiig: | Unit Of Measure: | | | |
| No Fiig: | | | | |
| Fiig: | Demilitarization: | | | |
| | No | | | |
| A07100 | Fiig: | | | |
| | A07100 | | | |
| | | | | |