

View Online at <https://aerobasegroup.com/nsn/4210-01-332-0793>

Tire Type:

Pneumatic

Charge Design Type:

Standard

Design Type:

Wheeled

Unit Type:

Charged

Capacity Rating:

150.0 pounds

Wheel Diameter:

Between 6.000 inches and 9.000 inches

Extinguishing Agent For Which Designed:

Bromochlorodifluoromethane

Extinguishing Agent Discharge Method:

Stored pressure

Cylinder Type:

Shatterproof

Special Features:

Agent: halon 1211; underwriter's lab rating: 30a/240b/1c; cylinder is certified dot 4bw240 w/operating pressure 200 psi, test pressure 480, burst pressure 960; operating temp range: neg 40 degrees to 120 degrees f; safety disk burst range: 400 to 500 psig; w/50 ft hose; dimension: 59 in h, 29 in. W, 36 in d; discharge range is 30-40 ft; discharge time: 44 seconds; not coast guard approved

Reference Data And Literature:

Service iaw af to. 13f4-4-141

Relationship To Similar Equipment:

Same as nsn 4210-01-140-2233, except for color; that is lime yellow, this is forrest green

Type/model Designation:

Model 600

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T278-b