

View Online at <https://aerobasegroup.com/nsn/4210-01-332-0793>

**Tire Type:**

Pneumatic

**Charge Design Type:**

Standard

**Design Type:**

Wheeled

**Unit Type:**

Charged

**Capacity Rating:**

150.0 pounds

**Wheel Diameter:**

Between 6.000 inches and 9.000 inches

**Extinguishing Agent For Which Designed:**

Bromochlorodifluoromethane

**Extinguishing Agent Discharge Method:**

Stored pressure

**Cylinder Type:**

Shatterproof

**Special Features:**

Agent: halon 1211; underwriter's lab rating: 30a/240b/1c; cylinder is certified dot 4bw240 w/operating pressure 200 psi, test pressure 480, burst pressure 960; operating temp range: neg 40 degrees to 120 degrees f; safety disk burst range: 400 to 500 psig; w/50 ft hose; dimension: 59 in h, 29 in. W, 36 in d; discharge range is 30-40 ft; discharge time: 44 seconds; not coast guard approved

**Reference Data And Literature:**

Service iaw af to. 13f4-4-141

**Relationship To Similar Equipment:**

Same as nsn 4210-01-140-2233, except for color; that is lime yellow, this is forrest green

**Type/model Designation:**

Model 600

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

T278-b