Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4210-01-383-2384

view Online at https://defobasegroup.com/nsn/+210-01-303-230+
Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.380 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response
Outside Diameter:
0.660 inches
Minimum Inside Bending Radius:
2.500 inches
Exterior Color:
Black
End Application:
Hemtt family (heavy expanded mobility tactical trucks)
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
End Fitting Component And Material:
Complete fitting steel all ends
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
18 2nd end
Burst Test Pressure:
16000.0 pounds per square inch
First End Swivel Action Capability:
Not included
Layer Composition And Location:
1st layer braided polyamide cord err-100
Maximum Operating Pressure:
4000.0 pounds per square inch
Thread Size:
0.562 inches 2nd end
Seat Angle:
37.0 degrees 2nd end
Flow Angle:
90.0 degrees 2nd end



Outer Covering Environmental Protection:

Hydraulic solution resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

57.000 inches

Second End Swivel Action Capability:

Not included

Special Features:

Inner conveying tube material-plastic, polyester

Thread Series Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0