Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4210-01-383-5804

Cross Sectional Shape:         Round         Thread Direction:         Right-hand 1st end         Inside Diameter:         0.625 inches         Tempurature Rating:         -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response         Outside Diameter:         0.906 inches         Minimum Inside Bending Radius:         5.000 inches         End Application:         4210-01-354-9893         Connection Style:         Plain 1st end         End Connection Design:         Straight 1st end         Connection Design:         Straight 1st end         Connection Type:         Threaded external pipe 1st end         Burst Test Pressure:         1400.0 pounds per square inch         Layer Composition And Location:         1st layer braided textile yarn and outer layer molded rubber, synthetic         Maximum Operating Pressure:         0.500 inches 1st end         Hydrostatic Test Pressure:         700.0 pounds per square inch         Hydrostatic Test Pressure:         700.0 pounds per square inch         Hydrostatic Test Pressure:         700.0 pounds per square inch         Hydrostatic Test Pressure:	
Thread Direction:         Right-hand 1st end         Inside Diameter:         0.625 inches         Tempurature Rating:         -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response         Outside Diameter:         0.906 inches         Minimum Inside Bending Radius:         5.000 inches         Part Application:         4210-01-354-9893         Connection Style:         Plain 1st end         End Connection Design:         Straight 1st end         Connection Type:         Threaded external pipe 1st end         Burst Test Pressure:         1400.0 pounds per square inch         Layer Composition And Location:         1st layer braided textile yarn and outer layer molded rubber, synthetic         Maximum Operating Pressure:         350.0 pounds per square inch         Hydrostatic Test Pressure:         0.000 inches 1st end         Hydrostati and weatherprof         Outer Covering Environmental Protection:         00.0 pounds per square inch         Hydrostati and weatherprof         Inside Surface Condition:         Smooth         Measuring Method And Length:         15.000 inches         Meal For Whic	Cross Sectional Shape:
Right-hand 1st end         Inside Diameter:         0.625 inches         Tempurature Rating:         -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response         Outside Diameter:         0.906 inches         Minimum Inside Bending Radius:         5.000 inches         End Application:         4210-01-354-9893         Connection Style:         Plain 1st end         End Connection Design:         Straight 1st end         Connection Type:         Threaded external pipe 1st end         Burst Test Pressure:         1400.0 pounds per square inch         Layer Composition And Location:         1st layer braided textrie yarn and outer layer molded rubber, synthetic         Maximum Operating Pressure:         0.000 pounds per square inch         Hydrostatic Test Pressure:         0.000 inches 1st end         Hydrostatic Test Pressure:         0.000 pounds per square inch         Hydrostatic Test Pressure:         100.0 pounds per square inch         Hydrostatic Test Pressure:         100.0 pounds per square inch         Hydrostatic Test Pressure:         1010 pounds per square inch         Hydrostatic Test Pressure:	
Inside Diameter: 0.625 inches 0.625 inches 0.625 inches 0.000 degrees fahrenheit and 200.0 degrees fahrenheit single response 0.000 inches 0.000 inc	
0.625 inches         Tempurature Rating:         -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response         Outside Diameter:         0.906 inches         Minimum Inside Bending Radius:         5.000 inches         End Application:         4210-01-354-9893         Connection Style:         Plain 1st end         End Connection Design:         Straight 1st end         Connection Type:         Threaded external pipe 1st end         Burst Test Pressure:         1400.0 pounds per square inch         Layer Composition And Location:         1st layer braided textile yam and outer layer molded rubber, synthetic         Maximum Operating Pressure:         95.00 pounds per square inch         Hydrostatic Test Pressure:         0.500 inches 1st end         Hydrostatic Test Pressure:         0.500 inches 1st end         Hydrostatic Test Pressure:         70.0 pounds per square inch         Outer Covering Environmental Protection:         Oil resistant and weatherproof         Inselstant and weatherproof         Inselstant and weatherproof         Masuring Method And Length:         15.500 inches         Meale For Which Designed: <th></th>	
Tempurature Rating:         -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response         Outside Diameter:         0.906 inches         Minimum Inside Bending Radius:         5.000 inches         End Application:         4210-01-354-9893         Connection Style:         Plain 1st end         End Connection Design:         Straight 1st end         Connection Type:         Threaded external pipe 1st end         Burst Test Pressure:         1400.0 pounds per square inch         Layer Composition And Location:         1st layer braided textile yarn and outer layer molded rubber, synthetic         Maximum Operating Pressure:         350.0 pounds per square inch         Lydrostatic Test Pressure:         0.500 inches 1st end         Hydrostatic Test Pressure:         0.500 inches 1st end         Hydrostatic Test Pressure:         0.500 inches 1st end         Hydrostatic Test Pressure:         0.500 inches 1st end         Macauring Method And Length:         15.500 inches         Masiang Method And Length:         15.500 inches         Hedia For Which Designed:         Fuel/oil, hydrocarbon single response <tr< th=""><th></th></tr<>	
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response         Outside Diameter:         0.906 inches         Minimum Inside Bending Radius:         5.000 inches         End Application:         4210-01-354-9893         Connection Style:         Plain 1st end         End Connection Design:         Straight 1st end         Connection Type:         Threaded external pipe 1st end         Burst Test Pressure:         1400.0 pounds per square inch         Layer Composition And Location:         1st layer braided textile yarn and outer layer molded rubber, synthetic         Maximum Operating Pressure:         350.0 pounds per square inch         Herd Size:         0.500 inches 1st end         Hydrostatic Test Pressure:         350.0 pounds per square inch         Herd Size:         0.500 inches 1st end         Hydrostatic Test Pressure:         0.500 inches 1st end         Muter Covering Environmental Protection:         Oil resistant and weatherproof         Inside Surface Condition:         Smoth         Measuring Method And Length:         15.500 inches         Fuel/oil, hydrocarbon single response	
Outside Diameter:0.906 inchesMinimum Inside Bending Radius:5.000 inchesEnd Application:4210-01-354-9893Connection Style:Plain 1st endEnd Connection Design:Straight 1st endConnection Type:Threaded external pipe 1st endBurst Test Pressure:1400.0 pounds per square inchLayer Composition And Location:1st layer braided textile yarn and outer layer molded rubber, syntheticMaximum Operating Pressure:350.0 pounds per square inchHydrostatic Test Pressure:0.500 inches 1st endHydrostatic Test Pressure:150.0 pounds per square inchOuter Covering Environmental Protection:Oil resistant and weatherproofInside Surface Condition:SmoothMeasuring Method And Length:15.500 inchesMedia For Which Designed:Fuel/oil, hydrocarbon single responseThread Steries Designator:Npt 1st endShelf Life:	
0.906 inchesMinimum Inside Bending Radius:5.000 inchesEnd Application:4210-01-354-9893Connection Style:Plain 1st endEnd Connection Design:Straight 1st endConnection Type:Threaded external pipe 1st endBurst Test Pressure:1400.0 pounds per square inchLayer Composition And Location:1st layer braided textile yarn and outer layer molded rubber, syntheticMaximum Operating Pressure:0.500 inches 1st endHydrostatic Test Pressure:0.500 inches 1st endMaximum Operating Pressure:0.500 inches 1st endHydrostatic Test Pressure:150.0 pounds per square inchDuter Covering Environmental Protection:Oil resistant and weatherproofInside Surface Condition:SmothMeasuring Method And Length:15.500 inchesHeile For Which Designed:Fuel/oil, hydrocarbon single responseThread Series Designator:Npt 1st endSheft Life:	
Minimu Inside Bending Radius: 5.000 inches End Application: 4210-01-354-9893 Connection Style: Plain 1st end End Connection Design: Straight 1st end Connection Type: Threaded external pipe 1st end Burst Test Pressure: 1400.0 pounds per square inch Layer Composition And Location: 1st layer braided textile yarn and outer layer molded rubber, synthetic Maximum Operating Pressure: 350.0 pounds per square inch Thread Size: 0.500 inches 1st end Hydrostatic Test Pressure: 700.0 pounds per square inch Ditres Size: 0.500 inches 1st end Hydrostatic Test Pressure: 700.0 pounds per square inch Ditre Covering Environmental Protection: Oil resistant and weatherproof Inside Surface Condition: Smooth Measuring Method And Length: 15.500 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Npt 1st end Sheff Life:	
5.000 inches         End Application:         4210-01-354-9893         Connection Style:         Plain 1st end         End Connection Design:         Straight 1st end         Connection Type:         Threaded external pipe 1st end         Burst Test Pressure:         1400.0 pounds per square inch         Layer Composition And Location:         1st layer braided textile yarn and outer layer molded rubber, synthetic         Maximum Operating Pressure:         350.0 pounds per square inch         Hydrostatic Test Pressure:         0,500 inches 1st end         Hydrostatic Test Pressure:         0,500 inches 1st end         Hydrostatic Test Pressure:         100.0 pounds per square inch         Ditter Covering Environmental Protection:         Oil resistant and weatherproof         Inside Surface Condition:         Smooth         Measuring Method And Length:         15.500 inches         Media For Which Designed:         Fuel/oil, hydrocarbon single response         Thread Size:         Puel/oil, hydrocarbon single response         Thread Size:         Npt 1st end         Shelf Life:	
End Application:   4210-01-354-9893   Connection Style:   Plain 1st end   End Connection Design:   Straight 1st end   Connection Type:   Threaded external pipe 1st end   Burst Test Pressure:   1400.0 pounds per square inch   Layer Composition And Location:   1st layer braided textile yarn and outer layer molded rubber, synthetic   Maximum Operating Pressure:   350.0 pounds per square inch   Thread Size:   0.500 inches 1st end   Hydrostatic Test Pressure:   700.0 pounds per square inch   Duter Covering Environmental Protection:   Oil resistant and weatherproof   Inside Surface Condition:   Smooth   Measuring Method And Length:   15.500 inches   Media For Which Designed:   Fuel/oil, hydrocarbon single response   Thread Sires Designator:   Npt 1st end   Shelf Life:	Minimum Inside Bending Radius:
4210-01-354-9893Connection Style:Plain 1st endEnd Connection Design:Straight 1st endConnection Type:Threaded external pipe 1st endBurst Test Pressure:1400.0 pounds per square inchLayer Composition And Location:1st layer braided textile yarn and outer layer molded rubber, syntheticMaximum Operating Pressure:350.0 pounds per square inchThread Size:0.300 inches 1st endHydrostatic Test Pressure:700.0 pounds per square inchOuter Covering Environmental Protection:Oil resistant and weatherproofInside Surface Condition:Stool inchesStool inchesMeasuring Method And Length:15.500 inchesMedia For Which Designed:Fuel/oil, hydrocarbon single responseThread Sires Designator:Npt 1st endShelf Life:	5.000 inches
Connection Style:Plain 1st endEnd Connection Design:Straight 1st endConnection Type:Threaded external pipe 1st endBurst Test Pressure:1400.0 pounds per square inchLayer Composition And Location:1st layer braided textile yarn and outer layer molded rubber, syntheticMaximum Operating Pressure:350.0 pounds per square inchThread Size:0.500 inches 1st endHydrostatic Test Pressure:700.0 pounds per square inchOuter Covering Environmental Protection:Oil resistant and weatherproofInside Surface Condition:SmoothMeasuring Method And Length:15.500 inchesHedia For Which Designed:Fuel/oil, hydrocarbon single responseThread Series Designator:Npt 1st endSheff Life:	End Application:
Plain 1st end         End Connection Design:         Straight 1st end         Connection Type:         Threaded external pipe 1st end         Burst Test Pressure:         1400.0 pounds per square inch         Layer Composition And Location:         1st layer braided textile yarn and outer layer molded rubber, synthetic         Maximum Operating Pressure:         350.0 pounds per square inch         Thread Size:         0.500 inches 1st end         Hydrostatic Test Pressure:         700.0 pounds per square inch         Outer Covering Environmental Protection:         Oil resistant and weatherproof         Inside Surface Condition:         Smooth         Measuring Method And Length:         15.500 inches         Media For Which Designed:         Fuel/oil, hydrocarbon single response         Thread Sires Designator:         Npt 1st end         Shelf Life:	4210-01-354-9893
End Connection Design:         Straight 1st end         Connection Type:         Threaded external pipe 1st end         Burst Test Pressure:         1400.0 pounds per square inch         Layer Composition And Location:         1st layer braided textile yarn and outer layer molded rubber, synthetic         Maximum Operating Pressure:         350.0 pounds per square inch         Thread Size:         0.500 inches 1st end         Hydrostatic Test Pressure:         700.0 pounds per square inch         Outer Covering Environmental Protection:         Oil resistant and weatherproof         Inside Surface Condition:         Smooth         Measuring Method And Length:         15.500 inches         Fuel/oil, hydrocarbon single response         Thread Series Designato::         Puel/oil, hydrocarbon single response         Sheft Life:	Connection Style:
Straight 1st end Connection Type: Threaded external pipe 1st end Burst Test Pressure: 1400.0 pounds per square inch Layer Composition And Location: 1st layer braided textile yarn and outer layer molded rubber, synthetic Maximum Operating Pressure: 350.0 pounds per square inch Thread Size: 0.500 inches 1st end Hydrostatic Test Pressure: 700.0 pounds per square inch Outer Covering Environmental Protection: Oil resistant and weatherproof Inside Surface Condition: Smooth Measuring Method And Length: 15.500 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Npt 1st end Shelf Life:	Plain 1st end
Connection Type:         Threaded external pipe 1st end         Burst Test Pressure:         1400.0 pounds per square inch         Layer Composition And Location:         1st layer braided textile yarn and outer layer molded rubber, synthetic         Maximum Operating Pressure:         350.0 pounds per square inch         Thread Size:         0.500 inches 1st end         Hydrostatic Test Pressure:         700.0 pounds per square inch         Outer Covering Environmental Protection:         Oil resistant and weatherproof         Inside Surface Condition:         Smooth         Measuring Method And Length:         15.500 inches         Media For Which Designed:         Fuel/oil, hydrocarbon single response         Thread Series Designator:         Npt 1st end         Shelf Life:	End Connection Design:
Threaded external pipe 1st end Burst Test Pressure: 1400.0 pounds per square inch Layer Composition And Location: 1st layer braided textile yarn and outer layer molded rubber, synthetic Maximum Operating Pressure: 350.0 pounds per square inch Thread Size: 0.500 inches 1st end Hydrostatic Test Pressure: 700.0 pounds per square inch Outer Covering Environmental Protection: Oil resistant and weatherproof Inside Surface Condition: Smooth Measuring Method And Length: 15.500 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Npt 1st end Shelf Life:	Straight 1st end
Burst Test Pressure:         1400.0 pounds per square inch         Layer Composition And Location:         1st layer braided textile yarn and outer layer molded rubber, synthetic         Maximum Operating Pressure:         350.0 pounds per square inch         Thread Size:         0.500 inches 1st end         Hydrostatic Test Pressure:         700.0 pounds per square inch         Outer Covering Environmental Protection:         Oil resistant and weatherproof         Inside Surface Condition:         Smooth         Measuring Method And Length:         15.500 inches         Media For Which Designed:         Fuel/oil, hydrocarbon single response         Thread Series Designator:         Npt 1st end         Shelf Life:	Connection Type:
<ul> <li>1400.0 pounds per square inch</li> <li>Layer Composition And Location:</li> <li>1st layer braided textile yarn and outer layer molded rubber, synthetic</li> <li>Maximum Operating Pressure:</li> <li>350.0 pounds per square inch</li> <li>Thread Size:</li> <li>0.500 inches 1st end</li> <li>Hydrostatic Test Pressure:</li> <li>700.0 pounds per square inch</li> <li>Outer Covering Environmental Protection:</li> <li>Oil resistant and weatherproof</li> <li>Inside Surface Condition:</li> <li>Smooth</li> <li>Measuring Method And Length:</li> <li>15.500 inches</li> <li>Media For Which Designed:</li> <li>Fuel/oil, hydrocarbon single response</li> <li>Thread Series Designator:</li> <li>Npt 1st end</li> <li>Shelf Life:</li> </ul>	Threaded external pipe 1st end
Layer Composition And Location:1st layer braided textile yarn and outer layer molded rubber, syntheticMaximum Operating Pressure:350.0 pounds per square inchThread Size:0.500 inches 1st endHydrostatic Test Pressure:700.0 pounds per square inchOuter Covering Environmental Protection:Oil resistant and weatherproofInside Surface Condition:SmoothMeasuring Method And Length:15.500 inchesMedia For Which Designed:Fuel/oil, hydrocarbon single responseThread Series Designator:Npt 1st endShelf Life:	Burst Test Pressure:
1 st layer braided textile yarn and outer layer molded rubber, syntheticMaximum Operating Pressure:350.0 pounds per square inchThread Size:0.500 inches 1st endHydrostatic Test Pressure:700.0 pounds per square inchOuter Covering Environmental Protection:Oil resistant and weatherproofInside Surface Condition:SmoothMeasuring Method And Length:15.500 inchesMedia For Which Designed:Fuel/oil, hydrocarbon single responseThread Series Designator:Npt 1st endShelf Life:	1400.0 pounds per square inch
Maximum Operating Pressure:350.0 pounds per square inchThread Size:0.500 inches 1st endHydrostatic Test Pressure:700.0 pounds per square inchOuter Covering Environmental Protection:Oil resistant and weatherproofInside Surface Condition:SmoothMeasuring Method And Length:15.500 inchesMedia For Which Designed:Fuel/oil, hydrocarbon single responseThread Series Designator:Npt 1st endShelf Life:	Layer Composition And Location:
350.0 pounds per square inch Thread Size: 0.500 inches 1st end Hydrostatic Test Pressure: 700.0 pounds per square inch Outer Covering Environmental Protection: Oil resistant and weatherproof Inside Surface Condition: Smooth Measuring Method And Length: 15.500 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Npt 1st end Shelf Life:	1st layer braided textile yarn and outer layer molded rubber, synthetic
Thread Size:0.500 inches 1st endHydrostatic Test Pressure:700.0 pounds per square inchOuter Covering Environmental Protection:Oil resistant and weatherproofInside Surface Condition:SmoothMeasuring Method And Length:15.500 inchesMedia For Which Designed:Fuel/oil, hydrocarbon single responseThread Series Designator:Npt 1st endShelf Life:	Maximum Operating Pressure:
0.500 inches 1st end Hydrostatic Test Pressure: 700.0 pounds per square inch Outer Covering Environmental Protection: Oil resistant and weatherproof Inside Surface Condition: Smooth Measuring Method And Length: 15.500 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Npt 1st end Shelf Life:	350.0 pounds per square inch
Hydrostatic Test Pressure:700.0 pounds per square inchOuter Covering Environmental Protection:Oil resistant and weatherproofInside Surface Condition:SmoothMeasuring Method And Length:15.500 inchesMedia For Which Designed:Fuel/oil, hydrocarbon single responseThread Series Designator:Npt 1st endShelf Life:	Thread Size:
700.0 pounds per square inch Outer Covering Environmental Protection: Oil resistant and weatherproof Inside Surface Condition: Smooth Measuring Method And Length: 15.500 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Npt 1st end Shelf Life:	0.500 inches 1st end
Outer Covering Environmental Protection:Oil resistant and weatherproofInside Surface Condition:SmoothMeasuring Method And Length:15.500 inchesMedia For Which Designed:Fuel/oil, hydrocarbon single responseThread Series Designator:Npt 1st endShelf Life:	Hydrostatic Test Pressure:
Oil resistant and weatherproofInside Surface Condition:SmoothMeasuring Method And Length:15.500 inchesMedia For Which Designed:Fuel/oil, hydrocarbon single responseThread Series Designator:Npt 1st endShelf Life:	700.0 pounds per square inch
Inside Surface Condition: Smooth Measuring Method And Length: 15.500 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Npt 1st end Shelf Life:	Outer Covering Environmental Protection:
Smooth Measuring Method And Length: 15.500 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Npt 1st end Shelf Life:	Oil resistant and weatherproof
Measuring Method And Length: 15.500 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Npt 1st end Shelf Life:	Inside Surface Condition:
15.500 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Npt 1st end Shelf Life:	Smooth
Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Npt 1st end Shelf Life:	Measuring Method And Length:
Fuel/oil, hydrocarbon single response Thread Series Designator: Npt 1st end Shelf Life:	15.500 inches
Thread Series Designator: Npt 1st end Shelf Life:	Media For Which Designed:
Npt 1st end Shelf Life:	Fuel/oil, hydrocarbon single response
Shelf Life:	Thread Series Designator:
	Npt 1st end
N/a	Shelf Life:
	N/a

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0