NSN 4210-01-501-1164

Fire Fighting Truck - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4210-01-501-1164

| view Online at https://aerobasegroup.com/hsh/4210-01-301-1104 |
|---|
| Prime Mover Quantity: |
| 1 |
| Length: |
| 75.000 feet |
| Prime Mover Type: |
| Diesel engine |
| Design Type: |
| Structural |
| Operation Method: |
| Hydraulic motor |
| Transmission Type: |
| Automatic |
| Pump Drive Type: |
| Power take-off |
| Pump Capacity: |
| 1250.0 gallons per minute |
| Pump Type: |
| Centrifugal |
| Tank Capacity: |
| 500.0 gallons |
| Extinguishing Agent For Which Designed: |
| Water |
| Water Tank Quantity: |
| 1 |
| Aerial Ladder: |
| Included |
| Chassis Size Designation: |
| 4x2 |
| Front Wheel Drive Feature: |
| Not included |
| Cab Design: |
| Closed |
| Product Name: |
| Truck, fire fighting (quint) |
| Special Features: |
| Red/blue strobe type warning lights; dual forward facing air horns; 100 watt electronic siren with volume control and selection of radio, pa, |
| manual, yelp, wail and hi-lo modes; cab roof mounted spotlights; four scene lights; 500 gal. Baffeled polypropylene water tank; 50 gal fuel |
| tank |
| Supplementary Features: |
| Capable of operating in temperatures: ranging from 32 to 125 degrees f, when specified will be equiped with a winterization system; the |
| vehicle is designed for operation at 2000 feet above sea level |

Unit Of Measure:

N/a

Shelf Life:

NSN 4210-01-501-1164

Fire Fighting Truck - Page 2 of 2



Demilitarization:

No

Fiig:

T278-a