Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4210-01-567-1283

Cross Sectional Shape:
Round
Inside Diameter:
0.6250 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response
Outside Diameter:
1.07 inches
Minimum Inside Bending Radius:
6.5 inches
Exterior Color:
Black
End Application:
Mrap - unique nsn - used on 5 mrap variants; mrap buffalo mk2a2; medium mine protected vehicle - mmpv
Connection Style:
Swivel nut with loose or integral clinch sleeve all ends
End Fitting Component And Material:
Swivel nut steel all ends
Fitting Component And Surface Treatment:
Body chromium and body zinc all ends
Thready Qty Per Inch (tpi):
12 all ends
Burst Test Pressure:
6000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided fiber
Maximum Operating Pressure:
1500.0 pounds per square inch
Thread Size:
1.0625 inches all ends
Measuring Method And Length:
10.0 inches
Product Name:
Feed hose, number 12
Special Features:
Inner tube: black, oil resistant nitril (btr); reinforcement: one fiber braid and one steel wire braid
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

NSN 4210-01-567-1283

Nonmetallic Hose Assembly - Page 2 of 2

Fiig: A542a0

