Reciprocating Compressor Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4310-00-073-3573

Compressor Quantity: 1 Uty Cycle In Percent: 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		
Duty Cycle In Percent: 100 Case For Which Designed: Air Discharge Flow Rate: 1.700 cubic feet per minute Discharge Pressure: 0.0000 pounds per square inch age Cooling System Design: Single Compressed Case Cooling Medium: Air Compressor Cooling Medium: Air Compressor Cooling Medium: Air Mounting Type: Base Reciprocating Compressor Design: Single Verind Arrangement Style: Vinder Arrangement Style: Vinder Arrangement Style: Verind besign Tatabet Connection Quantity: 1 Compressor Speed At Rated Capacity In Rpm: T25:0 Itake Connection Quantity: 2 Discharge Connection Type: Itake Connection Quantity: 2 Discharge Connection Type: Itake Connection Type: Reciprocating Mover Type: Recif molor Recif molor Redet Mover Type: </th <th>Compressor Quantity:</th> <th></th>	Compressor Quantity:	
100 Gas For Which Designed: Air Discharge Flow Rate: 1.700 cubic feet per minute Discharge Pressure: 60.000 pounds per square inch gage Cooling System Design: Single Compressed Gas Cooling Medium: Air Compressor Cooling Medium: Air Prine Mover Cooling Medium: Air Base Reciprocating Compressor Design: Single cubic Medium: Air Vointing Type: Base Reciprocating Compressor Design: Single acting Cylinder Quantity: 1 Variati design Stage Quantity: 1 Consection Quantity: 1 Consection Quantity: 1 Consection Quantity: 1 Consection Quantity: 1 Charbon Contion Quantity: 1 Discharge Connection Quantity: 2 Discharge Connection Type:		
Sar For Which Designet: Air Discharge Flow Rate: 1.700 cubic feet per minute Discharge Fressure: 60.000 pounds per square inch gage Couling System Design: Single Compressed Gas Cooling Medium: Air Compressor Cooling Medium: Air Prime Mover Cooling Medium: Air Base Prime Mover Cooling Medium: Air Single acting Prime Mover Cooling Medium: Air Single acting Prime Mover Cooling Medium: Air Single acting Single acting Valider Quantity: 1 Stage Quantity: 1 Stage Connection Quantity: 1 Stage Connection Quantity: 2 Discharge Connection Type: Contracting Connection Type: Discharge Connection Type: Discharge Connection Type: Bielet motor Stafet Direwort Type: Bielet motor	Duty Cycle In Percent:	
Air Discharge Flow Rate: 1.700 cubic feet per minute Discharge Pressure: 60000 pounds per square inch gage Couling System Design: Single Compressed Gas Cooling Medium: Air Compressor Cooling Medium: Air Prime Mover Cooling Medium: Air Botting Type: Base Reciprocating Compressor Design: Single acting Oylinder Quantity: 1 Vertical design Stage Quantity: 1 Cintac Connection Quantity: 1 Cintage Connection Quantity: 1 Discharge Connection Type: Cintage Connection Type: Threadel female Prime Mover Type: Recief vorice Recief vorice Side	100	
Discharge Frow Rate: 1.700 cubic feet per minute Discharge Pressure: 60.000 pounds per squere inch gage Cooling System Design: Cooling System Design: Compressed Gas Cooling Medium: Air Prime Mover Cooling Medium: Air Mounting Type: Base Reciprocting Compressor Design: Single acting Oylinder Arrangement Style: Vertical design Stage Quantity: 1 Compressor Speed At Rated Capacity In Rpm: 1725.0 Intake Connection Quantity: 2 Discharge Connection Type: Invaded female Prime Mover Type:	Gas For Which Designed:	
1.200 cubic feet per minute Discharge Pressure: 60.000 pounds per square inch gage Cooling System Design: Single Compressed Gas Cooling Medium: Air Compressor Cooling Medium: Air Prime Mover Cooling Medium: Air Mounting Type: Base Reciprocating Compressor Design: Single acting Oylinder Quantity: 1 Compressor Speed At Rated Capacity In Rpm: 1725.0 Intake Connection Quantity: 2 Discharge Connection Quantity: 2 Discharge Connection Quantity: 2 Discharge Connection Type: Heraded female Prime Mover Type: Electric motor Safety Device Type: Relef valie	Air	
Discharge Pressure:60.000 pounds per square inch gageCooling System Design:SingleCompressed Gas Cooling Medium:AirCompressor Cooling Medium:AirPrime Mover Cooling Medium:AirRoting Type:BaseReciprocating Compressor Design:Single actingOylinder Quantity:1Contract Style:Varical designStage Quantity:11Compressor Speed At Rated Capacity In Rpm:1725.0Interaction Quantity:211725.0Interaction Quantity:2112Discharge Connection Quantity:2131415151516161725.018191919192010212223242424252526262728282920	Discharge Flow Rate:	
80.000 pounds per square inch gage Cooling System Design: Single Compressed Gas Cooling Medium: Air Compressor Cooling Medium: Air Prime Mover Cooling Medium: Air Prime Mover Cooling Medium: Air Prime Mover Cooling Medium: Air Base Reciprocating Compressor Design: Single acting Cylinder Quantity: 1 Cylinder Arrangement Style: Varida design Stage Quantity: 1 Cylinder Arrangement Style: Varida design Stage Quantity: 1 Compressor Speed At Rated Capacity In Rpm: 1725.0 Instead Connection Quantity: 2 Discharge Connection Type: 172.0 Instead Genale Prime Mover Type: Instead Genale Prime Mover Type: Electric motor Safety Device Type: Rated Type Relief valve	1.700 cubic feet per minute	
Cooling System Design:SingleCompressed Gas Cooling Medium:AirCompressor Cooling Medium:AirPrime Mover Cooling Medium:AirMounting Type:BaseReciprocating Compressor Design:Single actingCylinder Quantity:1Cylinder Arrangement Style:Vertical designStage Quantity:11Compressor Speed At Rated Capacity In Rpm:1725.0Itatke Connection Quantity:2Joscharge Connection Quantity:2Pischarge Connection Type:Threaded femalePrime Mover Type:Electric motorSafety Perice Type:Relef valveCurrent Type And Rating In Amps:	Discharge Pressure:	
Single Compressed Gas Cooling Medium: Air Compressor Cooling Medium: Air Prime Mover Cooling Medium: Air Mounting Type: Base Reciprocating Compressor Design: Single acting Cylinder Quantity: 1 Cylinder Arangement Style: Vertiad design Stage Quantity: 1 Compressor Speed At Rated Capacity In Rpm: 1725.0 Intake Connection Quantity: 2 Discharge Connection Quantity: 2 Intexe Connection Quantity: 2 Discharge Connection Type: Threaded female Prime Mover Type: Electric motor Stafty Device Type: Relet valve Current Type And Rating In Amps:	60.000 pounds per square inch gage	
Compressed Gas Cooling Medium:AirCompressor Cooling Medium:AirPrime Mover Cooling Medium:AirMounting Type:BaseReciprocating Compressor Design:Single actingCylinder Quantity:1Cylinder Arrangement Style:Vatage Quantity:1Compressor Speed At Rated Capacity In Rpm:1725.0Intake Connection Quantity:2Discharge Connection Quantity:2Enderge Connection Type:1Electra motoPrime Mover Type:Electra motoStafey Device Type:Relef valveCompressor Speel At Rating In Amps:	Cooling System Design:	
Air Compressor Cooling Medium: Air Prime Mover Cooling Medium: Air Mounting Type: Base Reciprocating Compressor Design: Single acting Cylinder Quantity: 1 Cylinder Arrangement Style: Vertical design Stage Quantity: 1 Compressor Speed At Rated Capacity In Rpm: 1725.0 Intake Connection Quantity: 2 Discharge Connection Type: 1 Prime Mover Type: 1 Stafey Device Type: Electric motor Stafey Device Type: Relief valve Current Type And Rating In Amps:	Single	
Compressor Cooling Medium: Air Prime Mover Cooling Medium: Air Mounting Type: Base Reciprocating Compressor Design: Single acting Cylinder Quantity: 1 Cylinder Arrangement Style: Vertical design Stage Quantity: 1 Compressor Speed At Rated Capacity In Rpm: 1725.0 Intake Connection Quantity: 2 Discharge Connection Quantity: 2 Prime Mover Type: Electric motor Stept Device Type: Electric motor Stept Device Type: Relief valve	Compressed Gas Cooling Medium:	
AirPrime Mover Cooling Medium:AirMounting Type:BaseReciprocating Compressor Design:Single actingCylinder Quantity:1Cylinder Arrangement Style:Vertical designStage Quantity:1Compressor Speed At Rated Capacity In Rpm:1725.0Intake Connection Quantity:2Discharge Connection Quantity:2Pictead demalePrime Mover Type:Electric motorSafety Device Type:Relief valveCurrent Type And Rating In Amps:	Air	
Prime Mover Cooling Medium:AirMounting Type:BaseReciprocating Compressor Design:Single actingCylinder Quantity:1Cylinder Arrangement Style:Vertical designStage Quantity:1Compressor Speed At Rated Capacity In Rpm:1725.0Intake Connection Quantity:2Discharge Connection Quantity:2Pineaded femalePrime Mover Type:Electric motorSatey Device Type:Relief valveCurrent Type And Rating In Amps:	Compressor Cooling Medium:	
Air Mounting Type: Base Reciprocating Compressor Design: Single acting Cylinder Quantity: 1 Cylinder Arrangement Style: Vertical design Stage Quantity: 1 Compressor Speed At Rated Capacity In Rpm: 1725.0 Intake Connection Quantity: 2 Discharge Connection Quantity: 2 Discharge Connection Type: Threaded female Prime Mover Type: Electric motor Safety Device Type: Relief valve Current Type And Rating In Amps:	Air	
Nounting Type:BaseReciprocating Compressor Design:Single actingCylinder Quantity:1Cylinder Arrangement Style:Vertical designStage Quantity:11Compressor Speed At Rated Capacity In Rpm:1725.0Intake Connection Quantity:2Discharge Connection Quantity:2Discharge Connection Type:Threaded femalePrime Mover Type:Electric motorRelief valveCurrent Type And Rating In Anps:	Prime Mover Cooling Medium:	
Base Reciprocating Compressor Design: Single acting Cylinder Quantity: 1 Cylinder Arrangement Style: Vertical design Stage Quantity: 1 Compressor Speed At Rated Capacity In Rpm: 1725.0 Intake Connection Quantity: 2 Discharge Connection Quantity: 2 Pineaded female Prime Mover Type: Electric motor Stelet Payle Relet yalve Relet yalve Current Type And Rating In Amps:	Air	
Reciprocating Compressor Design: Single acting Cylinder Quantity: 1 Cylinder Arrangement Style: Vertical design Stage Quantity: 1 Compressor Speed At Rated Capacity In Rpm: 1725.0 Intake Connection Quantity: 2 Discharge Connection Quantity: 2 Pischarge Connection Type: Threaded female Prime Mover Type: Electric motor Safety Device Type: Relief valve Current Type And Rating In Amps:	Mounting Type:	
Single actingCylinder Quantity:1Cylinder Arrangement Style:Vertical designStage Quantity:1Compressor Speed At Rated Capacity In Rpm:1725.0Intake Connection Quantity:2Discharge Connection Quantity:2Discharge Connection Type:Threaded femalePrime Mover Type:Electric motorSafety Device Type:Relief valveCurrent Type And Rating In Amps:	Base	
Cylinder Quantity: 1 Cylinder Arrangement Style: Vertical design Stage Quantity: 1 Compressor Speed At Rated Capacity In Rpm: 1725.0 Intake Connection Quantity: 2 Discharge Connection Quantity: 2 Discharge Connection Type: Threaded female Prime Mover Type: Electric motor Safety Device Type: Relief valve Current Type And Rating In Amps:	Reciprocating Compressor Design:	
1 Cylinder Arrangement Style: Vertical design Stage Quantity: 1 Compressor Speed At Rated Capacity In Rpm: 1725.0 Intake Connection Quantity: 2 Discharge Connection Quantity: 2 Discharge Connection Type: Threaded female Prime Mover Type: Electric motor Safety Device Type: Relief valve Current Type And Rating In Amps:	Single acting	
Cylinder Arrangement Style:Vertical designStage Quantity:11Compressor Speed At Rated Capacity In Rpm:1725.0Intake Connection Quantity:2Discharge Connection Quantity:2Discharge Connection Type:Threaded femalePrime Mover Type:Electric motorSafety Device Type:Relief valveCurrent Type And Rating In Amps:	Cylinder Quantity:	
Vertical design Stage Quantity: 1 Compressor Speed At Rated Capacity In Rpm: Compressor Speed At Rated Capacity In Rpm: 1725.0 Intake Connection Quantity: 2 Intake Connection Quantity: 2 Discharge Connection Quantity: 2 Discharge Connection Quantity: 2 Discharge Connection Quantity: 2 Discharge Connection Type: 1 Threaded female Prime Mover Type: Electric motor Safety Device Type: Relief valve Current Type And Rating In Amps:	1	
Stage Quantity:1Compressor Speed At Rated Capacity In Rpm:1725.0Intake Connection Quantity:2Discharge Connection Quantity:2Discharge Connection Type:Threaded femalePrime Mover Type:Electric motorSafety Device Type:Relief valveCurrent Type And Rating In Amps:	Cylinder Arrangement Style:	
1 Compressor Speed At Rated Capacity In Rpm: 1725.0 Intake Connection Quantity: 2 Discharge Connection Quantity: 2 Discharge Connection Type: Threaded female Prime Mover Type: Electric motor Safety Device Type: Relief valve Current Type And Rating In Amps:	Vertical design	
Compressor Speed At Rated Capacity In Rpm:1725.0Intake Connection Quantity:2Discharge Connection Quantity:2Discharge Connection Type:Threaded femalePrime Mover Type:Electric motorSafety Device Type:Relief valveCurrent Type And Rating In Amps:	Stage Quantity:	
1725.0 Intake Connection Quantity: 2 Discharge Connection Quantity: 2 Discharge Connection Type: Discharge Connection Type: Phreaded female Prime Mover Type: Electric motor Safety Device Type: Relief valve Current Type And Rating In Amps:	1	
Intake Connection Quantity: 2 Discharge Connection Quantity: 2 Discharge Connection Type: Threaded female Prime Mover Type: Electric motor Safety Device Type: Relief valve	Compressor Speed At Rated Capacity In Rpm:	
2 Discharge Connection Quantity: 2 Discharge Connection Type: Threaded female Prime Mover Type: Electric motor Safety Device Type: Relief valve	1725.0	
Discharge Connection Quantity:2Discharge Connection Type:Threaded femalePrime Mover Type:Electric motorSafety Device Type:Relief valveCurrent Type And Rating In Amps:	Intake Connection Quantity:	
2 Discharge Connection Type: Threaded female Prime Mover Type: Electric motor Safety Device Type: Relief valve Current Type And Rating In Amps:	2	
Discharge Connection Type: Threaded female Prime Mover Type: Electric motor Safety Device Type: Relief valve Current Type And Rating In Amps:	Discharge Connection Quantity:	
Threaded female Prime Mover Type: Electric motor Safety Device Type: Relief valve Current Type And Rating In Amps:	2	
Prime Mover Type: Electric motor Safety Device Type: Relief valve Current Type And Rating In Amps:	Discharge Connection Type:	
Electric motor Safety Device Type: Relief valve Current Type And Rating In Amps:	Threaded female	
Safety Device Type: Relief valve Current Type And Rating In Amps:	Prime Mover Type:	
Relief valve Current Type And Rating In Amps:	Electric motor	
Current Type And Rating In Amps:	Safety Device Type:	
	Relief valve	
10 ac	Current Type And Rating In Amps:	
	1.0 ac	



Voltage In Volts And Current Type:

440.0 ac

Phase:

Three

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A026a0