

View Online at <https://aerobasegroup.com/nsn/4310-00-115-7752>

Brake Horsepower Required:

40.000

Mounting Type:

Base

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Flanged

Discharge Connection Quantity:

1

Discharge Connection Type:

Flanged

Drive Connection Type:

Multistrand v-belt

Body Surface Treatment:

Any acceptable

Furnished Items:

Belt guard

Overall Length:

46.000 inches

Overall Height:

66.250 inches

Overall Width:

37.500 inches

Current Type:

Ac

Cooling Medium:

Water

Vacuum Rating:

0.01 torr

Pump Quantity:

1

Pump Body Material:

Any acceptable

Specific Gas For Which Designed:

Air

Pumping Element Type:

Rotary piston

Intake Connection Flange Shape Style:

Round

Intake Connection Flange Outside Diameter:

13.500 inches

Intake Connection Flange Thickness:

1.312 inches

Intake Connection Bolt Hole Quantity:

8

Intake Connection Bolt Hole Diameter:

0.875 inches

Intake Connection Bolt Circle Diameter:

11.750 inches

Discharge Connection Flange Shape Style:

Round

Discharge Connection Flange Thickness:

1.062 inches

Discharge Connection Bolt Hole Quantity:

8

Discharge Connection Bolt Hole Diameter:

0.750 inches

Discharge Connection Bolt Circle Diameter:

7.500 inches

Operating Speed At Rated Capacity In Rpm:

614.0

Vapor Condensation Preventative Device:

Gas ballast valving

Air Displacement Rate:

850.0 cubic feet per minute in free air

System Design:

Noncorrosive

Prime Mover Type:

Electric motor

Current Rating In Amps:

98.0 and 49.0

Control Device Type:

Motor starter

Features Provided:

Separator tank

Discharge Connection Flange Outside Diameter:

9.000 inches

Voltage In Volts:

230.0 and 460.0

Phase:

Three

Special Features:

Pump assembly, vacuum

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A06700