Rotary Vacuum Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4310-00-150-6133

| Brake Horsepower Required: |
|---|
| 0.333 |
| Mounting Type: |
| Base |
| Stage Quantity: |
| 2 |
| Intake Connection Quantity: |
| 1 |
| Intake Connection Type: |
| Any acceptable |
| Discharge Connection Quantity: |
| 1 |
| Discharge Connection Type: |
| Threaded internal |
| Drive Connection Type: |
| Single strand v-belt |
| Body Surface Treatment: |
| Any acceptable |
| Overall Length: |
| 20.000 inches |
| Overall Height: |
| 17.000 inches |
| Overall Width: |
| 13.500 inches |
| Current Type: |
| Ac |
| Cooling Medium: |
| Air |
| Vacuum Rating: |
| 0.2 torr |
| Pump Quantity: |
| 1 |
| Pump Body Material: |
| Iron, cast |
| Specific Gas For Which Designed: |
| Air |
| Pumping Element Type: |
| Sliding vane |
| Operating Speed At Rated Capacity In Rpm: |
| 500.0 |
| Air Displacement Rate: |
| 1.8 cubic feet per minute in free air |
| |

NSN 4310-00-150-6133

Rotary Vacuum Pump Unit - Page 2 of 2



| System Design: |
|--|
| Noncorrosive |
| Prime Mover Type: |
| Electric motor |
| Current Rating In Amps: |
| 1.7 and 0.9 |
| Discharge Connection Thread Size And Series/type Designator: |
| 3/4-14 npt |
| Control Device Type: |
| Automatic speed regulator |
| Features Provided: |
| Fungus resistant treatment and separator tank |
| Voltage In Volts: |
| 230.0 and 460.0 |
| Phase: |
| Three |
| Frequency In Hertz: |
| 60.0 |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A06700 |