NSN 4310-00-203-4724

Reciprocating Vacuum Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4310-00-203-4724

| Brake Horsepower Required: |
|----------------------------------|
| 1.000 |
| Mounting Type: |
| Base |
| Cylinder Arrangement Style: |
| V design |
| Stage Quantity: |
| 1 |
| Intake Connection Quantity: |
| 1 |
| Intake Connection Type: |
| Threaded internal |
| Discharge Connection Quantity: |
| 1 |
| Discharge Connection Type: |
| Threaded internal |
| Drive Connection Type: |
| Multistrand v-belt |
| Body Surface Treatment: |
| Enamel |
| Overall Length: |
| 37.625 inches |
| Overall Height: |
| 16.750 inches |
| Overall Width: |
| 16.000 inches |
| Current Type: |
| Ac |
| Cooling Medium: |
| Air |
| Vacuum Rating: |
| 736.6 torr |
| Pump Quantity: |
| 1 |
| Pump Body Material: |
| Iron, cast |
| Specific Gas For Which Designed: |
| Air |
| Pumping Element Type: |
| Piston |
| Pump Cylinder Quantity: |

NSN 4310-00-203-4724 Reciprocating Vacuum Pump Unit - Page 2 of 2



| Operating Speed At Rated Capacity In Rpm: |
|--|
| 900.0 |
| Air Displacement Rate: |
| 18.0 cubic feet per minute in free air |
| System Design: |
| Noncorrosive |
| Prime Mover Type: |
| Electric motor |
| Current Rating In Amps: |
| 3.2 |
| Discharge Connection Thread Size And Series/type Designator: |
| 1.000-11-1/2 npt |
| Intake Connection Thread Size And Series/type Designator: |
| 1.000-11-1/2 npt |
| Voltage In Volts: |
| 230.0 |
| Phase: |
| Three |
| Frequency In Hertz: |
| 60.0 |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - - |
| Demilitarization: |
| No |
| Fiig: |
| A06700 |
| |