Rotary Vacuum Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4310-00-293-7574

| Droke II-              | reanower Beguired                                    |
|------------------------|--|
|                        | rsepower Required:                                   |
| 0.750                  | Turpo  |
| Mounting<br>Horizontal |  |
|                        |  |
| Stage Qu               | antity:  |
| 1<br>Intoko Co         | nnaction Quantity                                    |
|                        | nnection Quantity:                                   |
| 1<br>Intoko Co         | nnection Type:                                       |
| Threaded               |  |
|                        | e Connection Quantity:                               |
| 1                      | connection quantity.                                 |
|                        | Connection Type:                                     |
| Threaded               | e Connection Type:                                   |
|                        | internal   |
| Close cou              |  |
| Furnished              |  |
|                        | age and quantity sight gage and vacuum priming valve |
| Overall Lo             |  |
| 24.000 inc             |  |
| Overall H              |  |
| 21.750 inc             |  |
| Overall W              |  |
| 16.000 inc             |  |
| Current T              |  |
| Ac                     | · ·  |
|                        | ledium:  |
| Air                    |  |
| Vacuum F               | Rating:  |
| 381.0 torr             |  |
| Pump Qu                | antity:  |
| 1                      |  |
| Pump Bo                | dy Material:   |
| Bronze ma              | anganese, qq-I-225, comp 5-canceled                  |
| Specific C             | Gas For Which Designed:                              |
| Air                    |  |
| Pumping                | Element Type:  |
| Liquid pist            | on   |
| Operating              | Speed At Rated Capacity In Rpm:                      |
| 3500.0                 |  |
| Air Displa             | icement Rate:  |
| 5.0 cubic f            | eet per minute in free air                           |
|                        |  |

## NSN 4310-00-293-7574

Rotary Vacuum Pump Unit - Page 2 of 2



| System Design:   |  |
|--|--|
| Corrosive  |  |
| Prime Mover Type:  |  |
| Electric motor   |  |
| Current Rating In Amps:                                      |  |
| 1.2  |  |
| Discharge Connection Thread Size And Series/type Designator: |  |
| 3/4-14 npt   |  |
| Intake Connection Thread Size And Series/type Designator:    |  |
| 3/4-14 npt   |  |
| Safety Device Type:  |  |
| Safety relief valve  |  |
| Voltage In Volts:  |  |
| 440.0  |  |
| Phase:   |  |
| Three  |  |
| Frequency In Hertz:  |  |
| 60.0   |  |
| Shelf Life:  |  |
| N/a  |  |
| Unit Of Measure:   |  |
|  |  |
| Demilitarization:  |  |
| No   |  |
| Fiig:  |  |
| A06700   |  |