NSN 4310-00-307-3149

Rotary Vacuum Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4310-00-307-3149 **Brake Horsepower Required:** 0.500 **Mounting Type:** Base Stage Quantity: **Intake Connection Quantity: Intake Connection Type:** Threaded internal **Discharge Connection Quantity: Discharge Connection Type:** Threaded internal **Drive Connection Type:** Multistrand v-belt **Body Surface Treatment:** Any acceptable **Furnished Items:** Belt guard and v-belt **Overall Length:** Any acceptable **Overall Height:** Any acceptable Overall Width: Any acceptable **Current Type:** Ac **Cooling Medium:** Any acceptable Vacuum Rating: 0.2 millitorr **Pump Quantity: Pump Body Material:** Any acceptable **Specific Gas For Which Designed:** Air **Pumping Element Type:**

Rotary piston **Operating Speed At Rated Capacity In Rpm:** 1000.0

NSN 4310-00-307-3149Rotary Vacuum Pump Unit - Page 2 of 2



Err Default:
Err default
Vapor Condensation Preventative Device:
Gas ballast valving
Air Displacement Rate:
8.0 cubic feet per minute in free air
System Design:
Noncorrosive
Prime Mover Type:
Electric motor
Current Rating In Amps:
Any acceptable
Discharge Connection Thread Size And Series/type Designator:
0.750-14 npt
Intake Connection Thread Size And Series/type Designator:
1.000-11-1/2 npt
Control Device Type:
Constant speed
Safety Device Type:
High temperature shutdown switch
Features Provided:
Separator tank
Voltage In Volts:
115.0 and 230.0
Phase:
Single
Frequency In Hertz:
60.0
Cognizant Service:
Usaf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A06700