

View Online at <https://aerobasegroup.com/nsn/4310-00-368-3189>

**Brake Horsepower Required:**

0.500

**Mounting Type:**

Any acceptable

**Stage Quantity:**

1

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Threaded internal

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Threaded internal

**Drive Connection Type:**

Close coupled

**Furnished Items:**

Vacuum priming valve

**Current Type:**

Ac

**Cooling Medium:**

Any acceptable

**Vacuum Rating:**

355.6 torr

**Specific Gas For Which Designed:**

Air

**Pumping Element Type:**

Lobe

**Operating Speed At Rated Capacity In Rpm:**

3450.0

**Air Displacement Rate:**

5.2 cubic feet per minute in free air

**System Design:**

Corrosive

**Prime Mover Type:**

Electric motor

**Discharge Connection Thread Size And Series/type Designator:**

3/4-14 npt

**Intake Connection Thread Size And Series/type Designator:**

3/4-14 npt

**Voltage In Volts:**

440.0

**Phase:**

Three

**Frequency In Hertz:**

60.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A06700