

NSN 4310-00-520-3849 Rotary Vacuum Pump Unit - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4310-00-520-3849 **Brake Horsepower Required:** 7.500 **Mounting Type:** Base **Stage Quantity: Intake Connection Quantity: Intake Connection Type:** Flanged **Discharge Connection Quantity: Discharge Connection Type:** Threaded internal **Drive Connection Type:** Multistrand v-belt **Body Surface Treatment:** Any acceptable

**Overall Length:** 

40.630 inches

**Overall Height:** 

40.310 inches

**Overall Width:** 

33.690 inches

**Current Type:** 

Ac

**Cooling Medium:** 

Water

Vacuum Rating:

0.01 torr

**Pump Quantity:** 

**Pump Body Material:** 

Any acceptable

**Specific Gas For Which Designed:** 

**Pumping Element Type:** 

Rotary piston

Intake Connection Flange Shape Style:

**Intake Connection Flange Outside Diameter:** 

7.500 inches

## **NSN 4310-00-520-3849**Rotary Vacuum Pump Unit - Page 2 of 2



Intake Connection Flange Thickness:
0.900 inches
Intake Connection Bolt Hole Quantity:
4
Intake Connection Bolt Hole Diameter:
0.700 inches
Intake Connection Bolt Circle Diameter:
6.000 inches
Operating Speed At Rated Capacity In Rpm:
650.0
Vapor Condensation Preventative Device:
Gas ballast valving
Air Displacement Rate:
159.000 cubic feet per minute in free air
System Design:
Noncorrosive
Prime Mover Type:
Electric motor
Current Rating In Amps:
20.3 and 10.2
Discharge Connection Thread Size And Series/type Designator:
2-11-1/2 npt
Control Device Type:
Constant speed
Features Provided:
Fungus resistant treatment and separator tank
Voltage In Volts:
230.0 and 460.0
Phase:
Three
Frequency In Hertz:
60.0
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Filg:
A06700