NSN 4310-00-537-8876

Reciprocating Compressor Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4310-00-537-8876 **Compressor Quantity: Duty Cycle In Percent:** 100 **Gas For Which Designed:** Air **Discharge Flow Rate:** 15.000 cubic feet per minute **Discharge Pressure:** 175.000 pounds per square inch gage **Cooling System Design:** Single **Compressed Gas Cooling Medium: Compressor Cooling Medium: Prime Mover Cooling Medium:** Air **Gas Cooling Equipment Type:** Air type aftercooler and air type intercooler **Unloader Type:** Automatic **Mounting Type:** Horizontal tank **Reciprocating Compressor Design:** Single acting **Cylinder Quantity: Cylinder Arrangement Style:** Vertical design Stage Quantity: **Receiver Tank Capacity: Compressor Speed At Rated Capacity In Rpm:**

10.70 cubic feet 710.0 **Intake Connection Quantity:** 1 **Discharge Connection Quantity: Discharge Connection Type:** Threaded female

NSN 4310-00-537-8876

Reciprocating Compressor Unit - Page 2 of 2



| Silencer Type: |
|--|
| Inlet |
| Prime Mover Type: |
| Electric motor |
| Control Device Type: |
| Automatic start-stop and motor starter |
| Safety Device Type: |
| High pressure cutout and relief valve |
| Features Provided: |
| Fungus resistant treatment |
| Current Type And Rating In Amps: |
| 14.4 ac and 7.2 ac |
| Voltage In Volts And Current Type: |
| 230.0 ac or 460.0 ac |
| Brake Power Required: |
| 5.4 horsepower |
| Phase: |
| Three |
| Frequency In Hertz: |
| 60.0 |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| . |
| Demilitarization: |
| No |
| Fiig: |
| A026a0 |
| |