Reciprocating Compressor - Page 1 of 1

AeroBase Group

View Online at https://aerobasegroup.com/nsn/4310-00-572-2855

Air         Discharge Flow Rate:         Any acceptable         Discharge Pressror:         Any acceptable         Cooling System Design:         Mixed         Compressor Cooling Medium:         Fresh water         Urloader Type:         Automatic         Brace Horsepower Required:         1.000         Rate Horsepower Required:         1.001         Reliprocating Compressor Design:         Single acting         Cylinder Arrangement Style:         Veliade design         Stage Quantity:         1         Compressor Speed At Rated Capacity In Rpm:         Any acceptable         Instage Connection Quantity:         1         Discharge Connection Type:         Threaded female         Tempurature Rating Per Function:         Nate         Nate         Nate         Nate         Nate         Shelf Litt:         Nate         Shelf Litt:         Nate         Shelf Litt:         Nate         Shelf Litt:         Nate         Shelf Litt:     <		
Discharge Fressure:         Any acceptable         Ourga System Design:         Mixed         Compressor Cooling Medium:         Fresh watar         Unloader Type:         Automatic         Brake Horsepower Required:         1.600         Single acting         Cylinder Quantity:         2         Vertical design         Stage Quantity:         1         1         Compressor Sociend Quantity:         2         Stage Quantity:         1         1         Compacetable         Discharge Connection Quantity:         1	Gas For Which Designed:	
Any acceptable Discharge Pressure: Any acceptable Cooling System Design: Mixed Compressor Cooling Medium: Fresh water Unloader Type: Automatic Brake Morsepower Required: 1.800 Reciprocating Compressor Design: Single acting Cylinder Arrangement Style: Vertical design Stage Quantity: 1 Compressor Speed At Reted Capacity In Rpm: Any acceptable Intake Connection Quantity: 1 Single Connection Quantity: 1 Discharge Connection Type: Nature	Air	
Discharge Pressure: Any acceptable Cooling System Design: Mixed Compressor Cooling Medium: Fresh water Fresh water Unloader Type: Automatic Brake Horsepower Required: 1.000 Reciprocating Compressor Design: Single acting Cylinder Quantity: 2 Cylinder Arrangement Style: Vertical design Stage Quantity: 1 Compressor Speed At Rated Capacity In Rpm: Any acceptable Intake Connection Quantity: 1 Compressor Speed At Rated Capacity In Rpm: Any acceptable Intake Connection Quantity: 1 Discharge Connection Quantity: 1 Discharge Connection Type: Treaded female Tempurature Rating Per Function: Not rated Shef Life: Na Compressor Speed At Rated Capacity In Rpm: Any acceptable Intake Connection Quantity: 1 Discharge Connection Type: Treaded female Tempurature Rating Per Function: Not rated Shef Life: No Compressor Speed At Capacity In Compressor Capacity In Compressor Speed At Rated Capacity In Rpm: Any acceptable Intake Connection Quantity: 1 Discharge Connection Quantity: 1 Discharge Connection Type: Compressor Speed At Rated Capacity In Rpm: Any acceptable Intake Connection Quantity: 1 Discharge Connection Type: Compressor Speed At Rated Capacity In Rpm: Any acceptable Intake Connection Quantity: 1 Discharge Connection Quantity: 2 Discharge Connection Type: Compressor Speed At Rated Capacity In Rpm: Any acceptable Discharge Connection Type: Compressor Speed At Rated Capacity In Rpm: Compressor Spe		
Any acceptable Cooling System Design: Mixed Compressor Cooling Medium: Fresh water Unloader Type: Automatic Brake Horsepower Required: Automatic Brake Horsepower Required: Automatic Brake Horsepower Required: Automatic Brake Horsepower Required: Automatic Compressor Design: Single acting Cylinder Arrangement Style: Vertical design Cylinder Arrangement Style: Vertical design Cylinder Arrangement Style: Vertical design Compressor Speed At Rated Capacity In Rpm: Any acceptable Intake Connection Quantity: Compressor Speed At Rated Capacity In Rpm: Any acceptable Intake Connection Quantity: Compressor Speed At Rated Capacity In Rpm: Any acceptable Intake Connection Quantity: Compressor Speed At Rated Capacity In Rpm: Any acceptable Intake Connection Quantity: Compressor Speed At Rated Capacity In Rpm: Any acceptable Intake Connection Quantity: Compressor Speed At Rated Capacity In Rpm: Compressor Speed At Rated Capacity In Rpm: Any acceptable Intake Connection Quantity: Compressor Speed At Rated Capacity In Rpm: Compressor Speed At Rated Capacity		
Coling System Design:         Mixed         Compressor Cooling Medium:         Fresh water         Unloader Type:         Automatic         Brake Horsepower Required:         1.600         Brake Horsepower Required:         1.600         Reciprocating Compressor Design:         Single acting         Quilnder Quantity:         2         Cylinder Arrangement Style:         Vertical design         Stage Quantity:         1         1         Compressor Speed At Rated Capacity In Rpm:         Any acceptable         Intake Connection Quantity:         1         Discharge Connection Quantity:         1         Not rated         Storage Connection Quantity:         1         Discharge Connection Type:         Intake Connection Type:         Intake Connection Type:         Intake Connection Quantity:         1         Discharge Connection Type:         Intake Connection Type:         Intake Connection Type:         Intake Connection Type:         Intake Connection Stated         Discharge Connection Quantity: </td <td>Discharge Pressure:</td> <td></td>	Discharge Pressure:	
Mixed Compressor Cooling Medium: Fresh water Fresh water Unloader Type: Automatic Bake Horsepower Required: 1.400 Reciprocating Compressor Design: Single acting Conford Quantity: 2 Cylinder Arrangement Style: Vertical design Stage Quantity: 1 Compressor Speed At Rated Capacity in Rpm: Any acceptable Intake Connection Quantity: 1 Discharge Connection Type: Nreaded female Tempurature Rating Per Function: No rated Sheft Life: Na Discharge Connection: Na Discharge Connec	Any acceptable	
Compressor Cooling Medium:         Fresh water         Uhoader Type:         Automatic         Brake Horsepower Required:         1.600         Reciprocating Compressor Design:         Single acting         Cylinder Quantity:         2         Cylinder Arrangement Style:         Vertical design         Stage Quantity:         1         Compressor Speed At Rated Capacity In Rpm:         Any acceptable         Intake Connection Quantity:         1         Discharge Connection Quantity:         1         Discharge Connection Quantity:         1         Discharge Connection Type:         Threaded female         Tempurature Rating Per Function:         Not rated         Shelf Life:         Na         Uhi Of Measure:	Cooling System Design:	
Fresh water   Uhoader Type:   Automatic   Brake Horsepower Required:   1.800   Reciprocating Compressor Design:   Single acting   Cylinder Quantity:   2   Cylinder Arrangement Style:   Vertical design   Stage Quantity:   1   Compressor Speed At Rated Capacity In Rpm:   Any acceptable   Intake Connection Quantity:   1   1   Discharge Connection Type:   Threaded female   Threaded female   Shell Life:   Na   Na   Unit Reasure:	Mixed	
Unloader Type:         Automatic         Brake Horsepower Required:         1.600         Reciprocating Compressor Design:         Single acting         Oplinder Quantity:         2         Oplinder Arrangement Style:         Vertical design         Stage Quantity:         1         Compressor Speed At Rated Capacity In Rpm:         Any acceptable         Intake Connection Quantity:         1         Discharge Connection Quantity:         1         Discharge Connection Quantity:         1         Nated female         Toreaded female         Not rated         Shelf Life:         Na         Dird Measure:         -         Demilitarization:         Na         Fig:	Compressor Cooling Medium:	
Automatic Brake Horsepower Required: 1.600 Reciprocating Compressor Design: Single acting Cylinder Quantity: 2 Cylinder Arrangement Style: Vertical design Stage Quantity: 1 Compressor Speed At Rated Capacity In Rpm: Any acceptable Intake Connection Quantity: 1 Discharge Connection Quantity: 1 Discharge Connection Quantity: 1 Discharge Connection Quantity: 1 Nraeded female Tempurature Rating Per Function: Not rated Sheff Life: Na Composed Connection Quantity: Composed Connection Quantity: Composed Connection Connection Quantity: Composed Connection Connection Quantity: Composed Connection Connection Quantity: Composed Connection Connection Connection Connection Connection Connection Connection Connection Connection Co	Fresh water	
Brake Horsepower Required:  1.600 Reciprocating Compressor Design: Single acting Cylinder Quantity: 2 Cylinder Arrangement Style: Vertical design Stage Quantity: 1 Compressor Speed At Rated Capacity In Rpm: Any acceptable Intake Connection Quantity: 1 Discharge Connection Quantity: 1 Discharge Connection Type: Threaded female Tempurature Rating Per Function: Not rated Shelf Life: Na Unit Of Measure: Demilitarization: No Fig:	Unloader Type:	
1.600 Reciprocating Compressor Design: Single acting Cylinder Quantity: 2 Cylinder Arrangement Style: Vertical design Stage Quantity: Stage Quantity: Compressor Speed At Rated Capacity In Rpm: Any acceptable Intake Connection Quantity: 1 Discharge Connection Quantity: 1 Discharge Connection Type: Threaded female Tempurature Rating Per Function: Not rated Shelf Life: Na Unit Of Measure: Demilitarization: No Fig:	Automatic	
Reciprocating Compressor Design:   Single acting   Cylinder Quantity:   2   Sylinder Arrangement Style:   Vertical design   Stage Quantity:   1   Compressor Speed At Rated Capacity In Rpm:   Any acceptable   Intake Connection Quantity:   1   Discharge Connection Quantity:   1   1   Discharge Connection Quantity:   1   Not rated   Tempurature Rating Per Function:   Not rated   Shelf Life:   N/a   Unit Of Measure:   -   -   Penilitarization:   No   Fig:	Brake Horsepower Required:	
Single acting Cylinder Quantity: 2 Cylinder Arrangement Style: Vertical design Stage Quantity: 1 Compressor Speed At Rated Capacity In Rpm: Any acceptable Intake Connection Quantity: 1 Discharge Connection Quantity: 1 Discharge Connection Type: Threaded female Tempurature Rating Per Function: Not rated Shelf Life: Na Unit Of Measure:  Demilitarization: No Fig:	1.600	
Cylinder Quantity: 2 Cylinder Arrangement Style: Vertical design Stage Quantity: 1 Compressor Speed At Rated Capacity In Rpm: Any acceptable Intake Connection Quantity: 1 Discharge Connection Quantity: 1 Discharge Connection Quantity: 1 Discharge Connection Type: Threaded female Tempurature Rating Per Function: Not rated Shelf Life: Na Dir of Measure:  Demilitarization: No Fig:	Reciprocating Compressor Design:	
2 Cylinder Arrangement Style: Vertical design Stage Quantity: 1 Compressor Speed At Rated Capacity In Rpm: Any acceptable Intake Connection Quantity: 1 Discharge Connection Quantity: 1 Discharge Connection Type: Threaded female Tempurature Rating Per Function: Not rated Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:	Single acting	
Cylinder Arrangement Style: Vertical design Stage Quantity: 1 Compressor Speed At Rated Capacity In Rpm: Any acceptable Intake Connection Quantity: 1 Discharge Connection Quantity: 1 Discharge Connection Type: Threaded female Tempurature Rating Per Function: Not rated Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Cylinder Quantity:	
Vertical design Stage Quantity: 1 Compressor Speed At Rated Capacity In Rpm: Compressor Speed At Rated Capacity In Rpm: Any acceptable Intake Connection Quantity: 1 Intake Connection Quantity: 1 Discharge Connection Quantity: 1 Discharge Connection Quantity: 1 Discharge Connection Type: Threaded female Tempurature Rating Per Function: Not rated Shelf Life: Na Unit Of Measure: - Demilitarization: No Fig:	2	
Stage Quantity: 1 Compressor Speed At Rated Capacity In Rpm: Any acceptable Intake Connection Quantity: 1 Discharge Connection Quantity: 1 Ioscharge Connection Type: Threaded female Tempurature Rating Per Function: Not rated Sheff Life: N/a Unit Of Measure: Demilitarization: No Fig:	Cylinder Arrangement Style:	
1         Compressor Speed At Rated Capacity In Rpm:         Any acceptable         Intake Connection Quantity:         1         Discharge Connection Quantity:         1         Discharge Connection Type:         Threaded female         Tempurature Rating Per Function:         Not rated         Sheff Life:         N/a         Dint of Measure:            Demilitarization:         No         Fig:	Vertical design	
Compressor Speed At Rated Capacity In Rpm: Any acceptable Intake Connection Quantity: 1 Discharge Connection Quantity: 1 Discharge Connection Type: Threaded female Tempurature Rating Per Function: Not rated Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Stage Quantity:	
Any acceptable Intake Connection Quantity: 1 Discharge Connection Quantity: 1 I Discharge Connection Type: 1 Discharge Connection Type: Threaded female Tempurature Rating Per Function: Not rated Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	1	
Intake Connection Quantity: 1 Discharge Connection Quantity: 1 I Discharge Connection Type: Threaded female Theraded female Tempurature Rating Per Function: Not rated Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Compressor Speed At Rated Capacity In Rpm:	
1         Discharge Connection Quantity:         1         Discharge Connection Type:         Threaded female         Tempurature Rating Per Function:         Not rated         Shelf Life:         N/a         Unit Of Measure:            Demilitarization:         No         Fig:	Any acceptable	
Discharge Connection Quantity:         1         Discharge Connection Type:         Threaded female         Tempurature Rating Per Function:         Not rated         Shelf Life:         N/a         Unit Of Measure:            Demilitarization:         No         Fig:	Intake Connection Quantity:	
1         Discharge Connection Type:         Threaded female         Tempurature Rating Per Function:         Not rated         Shelf Life:         N/a         Unit Of Measure:            Pemilitarization:         No         Fig:	1	
Discharge Connection Type: Threaded female Tempurature Rating Per Function: Not rated Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:	Discharge Connection Quantity:	
Threaded female Tempurature Rating Per Function: Not rated Shelf Life: N/a Unit Of Measure: Demilitarization: No	1	
Tempurature Rating Per Function:   Not rated   Shelf Life:   N/a   Unit Of Measure:     Demilitarization:   No   Fig:	Discharge Connection Type:	
Not rated Shelf Life: N/a Unit Of Measure: Demilitarization: No	Threaded female	
Shelf Life:   N/a   Unit Of Measure:     Demilitarization:   No   Fig:	Tempurature Rating Per Function:	
N/a Unit Of Measure:  Demilitarization: No Fiig:	Not rated	
Unit Of Measure:  Demilitarization: No Fiig:	Shelf Life:	
 Demilitarization: No Fiig:	N/a	
No Fiig:	Unit Of Measure:	
No Fiig:		
Fiig:	Demilitarization:	
	No	
A026a0	Fiig:	
	A026a0	