## NSN 4310-00-650-9212

**Cross Sectional Shape:** 

Piston Connecting Rod - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4310-00-650-9212

oroso ocononar onape.
I-section type
Fabrication Method:
Cast
Shaft Connecting End Style:
Automotive standard split bearing 2 bolt
End Thickness:
1.000 inches
Edge Radius:
0.750 inches
End Hole Inside Diameter:
0.875 inches
Piston Connecting End Bearing:
Included
Bearing Replaceability:
Replaceable
Piston Connecting End Lubrication Drill Feature:
Included
Piston Connecting End Lubrication Method:
Full forced-feed
Shaft Connecting End Bearing:
Included
Shaft Connecting End Hole Inside Diameter:
1.875 inches
Shaft Connecting End Edge Radius:
1.250 inches
Shaft Connecting End Width:
3.156 inches
Shaft Connecting End Thickness:
1.562 inches
Shaft Connecting End Bearing Replaceability:
Replaceable
Shaft Connecting End Lubrication Drill Feature:
Included
Shaft Connecting End Lubrication Method:
Full forced-feed
Center To Center Effective Length:
6.250 inches
Body Width At Piston Connecting End:
1.062 inches
Body Width At Shaft Connecting End:
1.656 inches

## **NSN 4310-00-650-9212**Piston Connecting Rod - Page 2 of 2



Body Thickness At Piston Connecting End:
0.625 inches
Body Thickness At Shaft Connecting End:
0.625 inches
Piston End Connection Style:
Small engine and automotive standard
Material:
Steel
Material:
Steel
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: T267-d