

View Online at <https://aerobasegroup.com/nsn/4310-00-683-8850>

**Compressor Quantity:**

1

**Duty Cycle In Percent:**

100

**Gas For Which Designed:**

Air

**Discharge Flow Rate:**

15.000 cubic feet per minute

**Discharge Pressure:**

200.000 pounds per square inch gage

**Cooling System Design:**

Single

**Compressed Gas Cooling Medium:**

Air

**Compressor Cooling Medium:**

Air

**Prime Mover Cooling Medium:**

Air

**Gas Cooling Equipment Type:**

Air type aftercooler and air type intercooler

**Brake Horsepower Required:**

7.000

**Mounting Type:**

Wheel

**Rotary Compressor Design:**

Sliding vane

**Stage Quantity:**

2

**Compressor Speed At Rated Capacity In Rpm:**

Not rated

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Threaded female

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Threaded female

**Silencer Type:**

Discharge

**Unpackaged Unit Length:**

72.50 inches

**Unpackaged Unit Width:**

41.75 inches

**Unpackaged Unit Height:**

50.50 inches

**Prime Mover Type:**

Electric motor

**Control Device Type:**

Automatic start-stop

**Safety Device Type:**

Relief valve

**Features Provided:**

Fungus resistant treatment

**Current Type And Rating In Amps:**

14.0 ac and 7.0 ac

**Voltage In Volts And Current Type:**

230.0 ac or 460.0 ac

**Temperature Rating Per Function:**

Not rated

**Brake Power Required:**

7.000 horsepower

**Phase:**

Three

**Frequency In Hertz:**

60.0

**Functional Description:**

Used to provide a source of compressed air for operating paint spraying equipment and inflating tires

**Unpackaged Unit Weight:**

735.00 pounds

**Reference Data And Literature:**

Af to. 34y1-64-1

**Specification Or Standard:**

Mb-2 type

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A026a0