

View Online at <https://aerobasegroup.com/nsn/4310-00-683-8850>

Compressor Quantity:

1

Duty Cycle In Percent:

100

Gas For Which Designed:

Air

Discharge Flow Rate:

15.000 cubic feet per minute

Discharge Pressure:

200.000 pounds per square inch gage

Cooling System Design:

Single

Compressed Gas Cooling Medium:

Air

Compressor Cooling Medium:

Air

Prime Mover Cooling Medium:

Air

Gas Cooling Equipment Type:

Air type aftercooler and air type intercooler

Brake Horsepower Required:

7.000

Mounting Type:

Wheel

Rotary Compressor Design:

Sliding vane

Stage Quantity:

2

Compressor Speed At Rated Capacity In Rpm:

Not rated

Intake Connection Quantity:

1

Intake Connection Type:

Threaded female

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded female

Silencer Type:

Discharge

Unpackaged Unit Length:

72.50 inches

Unpackaged Unit Width:

41.75 inches

Unpackaged Unit Height:

50.50 inches

Prime Mover Type:

Electric motor

Control Device Type:

Automatic start-stop

Safety Device Type:

Relief valve

Features Provided:

Fungus resistant treatment

Current Type And Rating In Amps:

14.0 ac and 7.0 ac

Voltage In Volts And Current Type:

230.0 ac or 460.0 ac

Temperature Rating Per Function:

Not rated

Brake Power Required:

7.000 horsepower

Phase:

Three

Frequency In Hertz:

60.0

Functional Description:

Used to provide a source of compressed air for operating paint spraying equipment and inflating tires

Unpackaged Unit Weight:

735.00 pounds

Reference Data And Literature:

Af to. 34y1-64-1

Specification Or Standard:

Mb-2 type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A026a0