

View Online at <https://aerobasegroup.com/nsn/4310-00-693-2653>

Compressor Quantity:

1

Duty Cycle In Percent:

10

Gas For Which Designed:

Air

Discharge Flow Rate:

30.000 cubic feet per minute

Discharge Pressure:

250.000 pounds per square inch gage

Cooling System Design:

Single

Compressed Gas Cooling Medium:

Air

Compressor Cooling Medium:

Air

Prime Mover Cooling Medium:

Air

Unloader Type:

Automatic

Mounting Type:

Skid

Reciprocating Compressor Design:

Double acting

Cylinder Quantity:

4

Unable To Decode:

"v" design

Stage Quantity:

2

Receiver Tank Capacity:

16.00 cubic feet

Compressor Speed At Rated Capacity In Rpm:

640.0

Intake Connection Quantity:

2

Unpackaged Unit Length:

80.00 inches

Prime Mover Type:

Electric motor

Control Device Type:

Automatic start-stop

Safety Device Type:

Relief valve

Features Provided:

Fungus resistant treatment

Current Type And Rating In Amps:

25.2 ac and 12.5 ac

Voltage In Volts And Current Type:

230.0 ac or 460.0 ac

Brake Power Required:

10.0 horsepower

Phase:

Three

Frequency In Hertz:

60.0

Functional Description:

Electric motor driven and used to operate small pneumatic tools, grease guns, paint guns, and other items requiring a clean source of compressed air; used in shops, hangers and paint shops

Reference Data And Literature:

Af to. 34y1-90-1

Specification Data:

81349-mil-c-26811 government specification

Specification Or Standard:

Mb-8 type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A026a0