Rotary Vacuum Pump Unit - Page 1 of 2





**Brake Horsepower Required:** 0.333 Mounting Type: Base **Stage Quantity:** 1 Intake Connection Quantity: 1 Intake Connection Type: Threaded internal **Discharge Connection Quantity:** 1 **Discharge Connection Type:** Threaded internal **Drive Connection Type:** Single strand v-belt **Body Surface Treatment:** Any acceptable **Overall Length:** Any acceptable **Overall Height:** Any acceptable **Overall Width:** Any acceptable **Current Type:** Ac **Cooling Medium:** Air Vacuum Rating: 50.8 torr **Pump Quantity:** 1 **Pump Body Material:** Any acceptable Specific Gas For Which Designed: Air **Pumping Element Type:** Sliding vane **Operating Speed At Rated Capacity In Rpm:** 1725.0 Air Displacement Rate: 5.9 cubic feet per minute in free air

## NSN 4310-00-711-7413

Rotary Vacuum Pump Unit - Page 2 of 2



System Design:
Noncorrosive
Prime Mover Type:
Electric motor
Current Rating In Amps:
Any acceptable
Discharge Connection Thread Size And Series/type Designator:
3/8-18 npt
Intake Connection Thread Size And Series/type Designator:
3/8-18 npt
Voltage In Volts:
115.0 and 230.0
Phase:
Single
Frequency In Hertz:
60.0
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A06700