

View Online at <https://aerobasegroup.com/nsn/4310-00-838-0169>

Brake Horsepower Required:

10.000

Mounting Type:

Base

Cylinder Arrangement Style:

Vertical design

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Flanged

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Drive Connection Type:

Multistrand v-belt

Body Surface Treatment:

Any acceptable

Furnished Items:

Quantity sight gage

Current Type:

Ac

Cooling Medium:

Water

Vacuum Rating:

0.01 torr

Pump Quantity:

1

Pump Body Material:

Any acceptable

Specific Gas For Which Designed:

Air

Pumping Element Type:

Piston

Pump Cylinder Quantity:

1

Intake Connection Flange Shape Style:

Round

Intake Connection Flange Outside Diameter:

11.000 inches

Operating Speed At Rated Capacity In Rpm:

419.0

Vapor Condensation Preventative Device:

Gas ballast valving

Air Displacement Rate:

218.0 cubic feet per minute in free air

System Design:

Noncorrosive

Prime Mover Type:

Electric motor

Current Rating In Amps:

13.3

Discharge Connection Thread Size And Series/type Designator:

3.000-8 npt

Control Device Type:

Constant speed

Safety Device Type:

High temperature shutdown switch and low pressure oil shutdown switch

Features Provided:

Fungus resistant treatment and separator tank

Voltage In Volts:

460.0

Phase:

Three

Frequency In Hertz:

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A06700