NSN 4310-01-247-4066

Rotary Vacuum Pump - Page 1 of 2

Brake Horsepower Required:

0.500



View Online at https://aerobasegroup.com/nsn/4310-01-247-4066

level ga, draincock & manual; initial supply + 1 ex qt oil is furn

Stage Quantity:
2
Intake Connection Quantity:
1
Intake Connection Type:
Unthreaded external
Discharge Connection Quantity:
1
Discharge Connection Type:
Any acceptable
Body Surface Treatment:
Any acceptable
Overall Length:
17.875 inches
Overall Height:
15.750 inches
Overall Width:
12.750 inches
Cooling Medium:
Oil
Vacuum Rating:
0.1 millitorr
Pump Body Material:
Any acceptable
Specific Gas For Which Designed:
Air
Pumping Element Type:
Any acceptable
Intake Connection Outside Diameter:
1.220 inches
Operating Speed At Rated Capacity In Rpm:
525.0
Vapor Condensation Preventative Device:
Gas ballast valving
Air Displacement Rate:
4.9 cubic feet per minute in free air
System Design:
Noncorrosive
Special Features:
Recovery time 1 to 2 min; int valve controlled lub; shipping wt 135 lbs; comes equipped w/ 1/2 hp mtr w/ pulley & v-belt, belt guard, sight oil

NSN 4310-01-247-4066

Rotary Vacuum Pump - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A06700