## NSN 4310-01-339-6019

Rotary Vacuum Pump - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4310-01-339-6019

Stage Quantity:
1
Intake Connection Quantity:
1
Discharge Connection Quantity:
1
Discharge Connection Type:
Flanged
Vacuum Rating:
0.1 microtorr
Pump Body Material:
Aluminum alloy
Pumping Element Type:
Sliding vane
Operating Speed At Rated Capacity In Rpm:
Operating Speed At Rated Capacity In Rpm: 1725.0
1725.0
1725.0 Air Displacement Rate:
1725.0  Air Displacement Rate: 7.0 cubic feet per minute in free air
1725.0  Air Displacement Rate: 7.0 cubic feet per minute in free air  System Design:
1725.0  Air Displacement Rate: 7.0 cubic feet per minute in free air  System Design:  Noncorrosive
1725.0  Air Displacement Rate: 7.0 cubic feet per minute in free air  System Design:  Noncorrosive  Shelf Life:
Air Displacement Rate: 7.0 cubic feet per minute in free air System Design: Noncorrosive Shelf Life: N/a
Air Displacement Rate: 7.0 cubic feet per minute in free air System Design: Noncorrosive Shelf Life: N/a Unit Of Measure:
Air Displacement Rate: 7.0 cubic feet per minute in free air System Design: Noncorrosive Shelf Life: N/a Unit Of Measure:
Air Displacement Rate: 7.0 cubic feet per minute in free air System Design: Noncorrosive Shelf Life: N/a Unit Of Measure: Demilitarization:
Air Displacement Rate: 7.0 cubic feet per minute in free air System Design: Noncorrosive Shelf Life: N/a Unit Of Measure: Demilitarization: No