NSN 4310-01-344-1037

Rotary Vacuum Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4310-01-344-1037 **Brake Horsepower Required:** 0.250 **Mounting Type:** Base **Stage Quantity: Intake Connection Quantity: Intake Connection Type:** Threaded internal **Discharge Connection Quantity: Current Type:** Ac Vacuum Rating: 26.0 inches of mercury **Pump Quantity: Pump Body Material:** Iron, cast **Specific Gas For Which Designed:** Air **Pumping Element Type:** Rotary piston **Operating Speed At Rated Capacity In Rpm:** 1725.0 Air Displacement Rate: 4.0 cubic feet per minute in free air **Minimum Operating Temp:** 32.0 degrees fahrenheit System Design: Noncorrosive **End Application:** A/f-18-dcn **Prime Mover Type:** Electric motor **Current Rating In Amps:** Intake Connection Thread Size And Series/type Designator:

1.652 1/4-18 npt **Control Device Type:** Automatic speed regulator

NSN 4310-01-344-1037

Rotary Vacuum Pump Unit - Page 2 of 2



| Safety Device Type: | | | | |
|---|--------------------------|-----------------|--------------------------|----------------------|
| Safety relief valve | | | | |
| Err Default: | | | | |
| Err default | | | | |
| Err Default: | | | | |
| Err default | | | | |
| Voltage In Volts: | | | | |
| 115.0 | | | | |
| Phase: | | | | |
| Single | | | | |
| Special Features: | | | | |
| Unit includes components of repair set: | elbow assembly an914-2d; | light 5m2445-5; | light assembly 5m943-21; | gage 7m728-1; vacuum |
| gage 7m728-2 | | | | |
| Frequency In Hertz: | | | | |
| 60.0 | | | | |
| Shelf Life: | | | | |
| N/a | | | | |
| Unit Of Measure: | | | | |
| | | | | |
| Demilitarization: | | | | |
| Yes - demil/mli | | | | |
| Fiig: | | | | |
| A06700 | | | | |