

View Online at <https://aerobasegroup.com/nsn/4310-01-345-2505>

Compressor Quantity:

1

Duty Cycle In Percent:

Not rated

Gas For Which Designed:

Air

Discharge Flow Rate:

0.950 cubic feet per minute

Discharge Pressure:

10.000 pounds per square inch gage

Cooling System Design:

Single

Compressor Cooling Medium:

Air

Prime Mover Cooling Medium:

Air

Brake Horsepower Required:

0.100

Mounting Type:

Base

Rotary Compressor Design:

Sliding vane

Stage Quantity:

1

Compressor Speed At Rated Capacity In Rpm:

3450.0

Intake Connection Quantity:

1

Intake Connection Type:

Threaded female

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded female

Unpackaged Unit Length:

6.320 inches

Unpackaged Unit Width:

4.190 inches

Unpackaged Unit Height:

4.000 inches

Prime Mover Type:

Electric motor

Current Type And Rating In Amps:

2.3 ac and 2.0 ac

Voltage In Volts And Current Type:

115.0 ac

Temperature Rating Per Function:

Not rated

Brake Power Required:

0.100 horsepower

Phase:

Single

Special Features:

Brpm at 50.0 hz is 2850.0; 0.125-27 npt inlet/outlet sz; filter and muffler ports are plugged; operating temp range 0.0 to 38.0 degrees c; can be used as a vacuum pump by reversing inlet/outlet ports

Frequency In Hertz:

50.0 and 60.0

Unpackaged Unit Weight:

7.00 pounds

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A026a0