

View Online at <https://aerobasegroup.com/nsn/4310-01-463-1152>

**Mounting Type:**

Bracket bottom side

**Filtration Rating In Microns:**

10.0 absolute

**End Application:**

Compressor; w/s: forrestal class cv; tarawa class lha; supply class aoe; arleigh burke class ddg; emory s. Land class as

**Design Type:**

Reusable

**Unit Quantity:**

4

**Bracket Quantity:**

1

**Filtering Element Quantity:**

1

**Criticality Code Justification:**

Feat

**First Intake Connection Type:**

Plain face flange side

**First Discharge Connection Relationship To Intake Connection:**

Not identical

**First Discharge Connection Type:**

Unthreaded external tube top

**Err Default:**

Err default

**First Intake Flange Outside Diameter:**

8.500 inches

**First Intake Flange Shape Style:**

Round w/unthreaded bolt holes

**First Intake Flange Face Style:**

Plain

**First Intake Flange Thickness:**

0.890 inches

**Special Features:**

Assembly contains: filter/silencer p/n: fru-04-x0278, material: 304 ss; replacement element p/n 12350e4 (10 micro rating); band assembly (2 req) p/n rmb10-0001, except fasteners to be hex head bolts with esna lock nuts; restriction indicator rbx00-2277; gasket; cover assembly (304 ss); length: 35.250 in.; outside diameter: 10.150 in.; weapon system essential.

**Material:**

Steel comp 304 body

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A24000