

View Online at <https://aerobasegroup.com/nsn/4310-01-463-1152>

Mounting Type:

Bracket bottom side

Filtration Rating In Microns:

10.0 absolute

End Application:

Compressor; w/s: forrestal class cv; tarawa class lha; supply class aoe; arleigh burke class ddg; emory s. Land class as

Design Type:

Reusable

Unit Quantity:

4

Bracket Quantity:

1

Filtering Element Quantity:

1

Criticality Code Justification:

Feat

First Intake Connection Type:

Plain face flange side

First Discharge Connection Relationship To Intake Connection:

Not identical

First Discharge Connection Type:

Unthreaded external tube top

Err Default:

Err default

First Intake Flange Outside Diameter:

8.500 inches

First Intake Flange Shape Style:

Round w/unthreaded bolt holes

First Intake Flange Face Style:

Plain

First Intake Flange Thickness:

0.890 inches

Special Features:

Assembly contains: filter/silencer p/n: fru-04-x0278, material: 304 ss; replacement element p/n 12350e4 (10 micro rating); band assembly (2 req) p/n rmb10-0001, except fasteners to be hex head bolts with esna lock nuts; restriction indicator rbx00-2277; gasket; cover assembly (304 ss); length: 35.250 in.; outside diameter: 10.150 in.; weapon system essential.

Material:

Steel comp 304 body

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A24000