

View Online at <https://aerobasegroup.com/nsn/4320-00-033-4955>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Current Type:

Dc

Media For Which Designed:

Hydrocarbon fuels and oils

Environmental Protection:

Dust-ignition proof

Pump Quantity:

1

Maximum Discharge Flow Rate:

0.5 gallons per minute

Discharge Pressure:

1000.0 pounds per square inch gage

Operating Speed At Rated Capacity:

8000.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Rotary Pump Design:

Gear

Operation Relationship Design:

Simultaneous

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

1.5

Discharge Connection Thread Size And Series/type Designator:

0.437-20 unf

Intake Connection Thread Size And Series/type Designator:

0.562-18 unf

Prime Mover Power Rating:

0.437 horsepower

Voltage In Volts:

26.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A19400