NSN 4320-00-038-3419

Rotary Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-00-038-3419

Prime Mover Quantity:
1
Intake Connection Quantity:
1
Intake Connection Type:
Threaded internal
Discharge Connection Quantity:
2
Discharge Connection Type:
Threaded internal
Current Type:
Dc
Media For Which Designed:
Alcohol and water, fresh
Environmental Protection:
Explosion proof
Pump Quantity:
1
Maximum Discharge Flow Rate:
0.1 gallons per minute
Discharge Pressure:
20.0 pounds per square inch gage
Operating Speed At Rated Capacity:
12000.0 revolutions per minute
Pumping Element Operating Position:
Horizontal
Volume Control Type:
Rotary
Control Location:
Center
Prime Mover Type:
Electric motor
Inclosure Type:
Fully enclosed
Current Rating In Amps:
1.8
Discharge Connection Thread Size And Series/type Designator:
0.405-27 npt
Intake Connection Thread Size And Series/type Designator:
0.405-27 npt
Prime Mover Power Rating:
0.013 horsepower

NSN 4320-00-038-3419

Rotary Pump Unit - Page 2 of 2



V	o	lta	ae	In	ν	ol	ts:
v	v	ııa	uc		v	vi	w.

27.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400