NSN 4320-00-052-3273

Rotary Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-00-052-3273

Prime Mover Quantity:
1
Prime Mover Cooling Medium:
Air
Intake Connection Quantity:
1
Intake Connection Type:
Threaded internal
Discharge Connection Quantity:
1
Discharge Connection Type:
Threaded internal
Current Type:
Ac
Pump Quantity:
1
Cooling Method:
Air to air cooled
Maximum Discharge Flow Rate:
3.000 gallons per minute
Operating Speed At Rated Capacity:
1425.0 revolutions per minute
Pumping Element Operating Position:
Horizontal
Rotary Pump Design:
Gear
Prime Mover Type:
Electric motor
Inclosure Type:
Fully enclosed
Discharge Connection Thread Size And Series/type Designator:
0.500-14 npt
Intake Connection Thread Size And Series/type Designator:
0.500-14 npt
Prime Mover Power Rating:
0.333 horsepower
Voltage In Volts:
115.0 and 230.0
Phase:
Single
Frequency In Hertz:
50.0

NSN 4320-00-052-3273

Rotary Pump Unit - Page 2 of 2



Reference	Number	Differentiating	Characteristics:
11010101100	HUIIDEI	Differentiation	Ullai actel istics.

As differentiated by electric motor power unit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400