NSN 4320-00-061-9258

Reciprocating Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-00-061-9258

Prime Mover Quantity:
1
Prime Mover Cooling Medium:
Air
Mounting Type:
Base
Cylinder Quantity:
1
Intake Connection Quantity:
1
Intake Connection Type:
Threaded internal
Discharge Connection Quantity:
1
Discharge Connection Type:
Threaded internal
Current Type:
Ac
Environmental Protection:
Dripproof
Pump Quantity:
1
Pumping Element Type:
Piston
Cooling Method:
Air to air cooled
7 til to all oooloa
Maximum Discharge Flow Rate:
Maximum Discharge Flow Rate:
Maximum Discharge Flow Rate: 0.005 gallons per minute
Maximum Discharge Flow Rate: 0.005 gallons per minute Discharge Pressure:
Maximum Discharge Flow Rate: 0.005 gallons per minute Discharge Pressure: 1000.0 pounds per square inch gage
Maximum Discharge Flow Rate: 0.005 gallons per minute Discharge Pressure: 1000.0 pounds per square inch gage Total Head:
Maximum Discharge Flow Rate: 0.005 gallons per minute Discharge Pressure: 1000.0 pounds per square inch gage Total Head: 2300.000 feet
Maximum Discharge Flow Rate: 0.005 gallons per minute Discharge Pressure: 1000.0 pounds per square inch gage Total Head: 2300.000 feet Operating Speed At Rated Capacity:
Maximum Discharge Flow Rate: 0.005 gallons per minute Discharge Pressure: 1000.0 pounds per square inch gage Total Head: 2300.000 feet Operating Speed At Rated Capacity: 29.0 strokes per minute
Maximum Discharge Flow Rate: 0.005 gallons per minute Discharge Pressure: 1000.0 pounds per square inch gage Total Head: 2300.000 feet Operating Speed At Rated Capacity: 29.0 strokes per minute Pumping Element Operating Position:
Maximum Discharge Flow Rate: 0.005 gallons per minute Discharge Pressure: 1000.0 pounds per square inch gage Total Head: 2300.000 feet Operating Speed At Rated Capacity: 29.0 strokes per minute Pumping Element Operating Position: Horizontal
Maximum Discharge Flow Rate: 0.005 gallons per minute Discharge Pressure: 1000.0 pounds per square inch gage Total Head: 2300.000 feet Operating Speed At Rated Capacity: 29.0 strokes per minute Pumping Element Operating Position: Horizontal Pump Reciprocating Design:
Maximum Discharge Flow Rate: 0.005 gallons per minute Discharge Pressure: 1000.0 pounds per square inch gage Total Head: 2300.000 feet Operating Speed At Rated Capacity: 29.0 strokes per minute Pumping Element Operating Position: Horizontal Pump Reciprocating Design: Single acting
Maximum Discharge Flow Rate: 0.005 gallons per minute Discharge Pressure: 1000.0 pounds per square inch gage Total Head: 2300.000 feet Operating Speed At Rated Capacity: 29.0 strokes per minute Pumping Element Operating Position: Horizontal Pump Reciprocating Design: Single acting Reciprocating Stroke Type:

NSN 4320-00-061-9258

Reciprocating Pump Unit - Page 2 of 2



Inclosure Type:
Partially enclosed
Discharge Connection Thread Size And Series/type Designator:
0.500-14 npt
Intake Connection Thread Size And Series/type Designator:
0.500-14 npt
Prime Mover Power Rating:
0.333 horsepower
Voltage In Volts:
115.0
Phase:
Single
Frequency In Hertz:
60.0
Reference Number Differentiating Characteristics:
By power unit
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A19400