NSN 4320-00-063-9617

Rotary Pump Unit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4320-00-063-9617

Prime Mover Quantity:

Prime Mover Quantity:
1
Prime Mover Cooling Medium:
Air
Intake Connection Quantity:
1
Intake Connection Type:
Oval flange
Discharge Connection Quantity:
1
Discharge Connection Type:
Oval flange
Current Type:
Ac
Pump Quantity:
1
Cooling Method:
Air to air cooled
End Application:
An/alq-119
Maximum Discharge Flow Rate:
3.0 gallons per minute
-
3.0 gallons per minute
3.0 gallons per minute Discharge Pressure:
3.0 gallons per minute Discharge Pressure: 145.0 pounds per square inch gage
3.0 gallons per minute Discharge Pressure: 145.0 pounds per square inch gage Pumping Element Operating Position:
3.0 gallons per minute Discharge Pressure: 145.0 pounds per square inch gage Pumping Element Operating Position: Horizontal
3.0 gallons per minute Discharge Pressure: 145.0 pounds per square inch gage Pumping Element Operating Position: Horizontal Prime Mover Type:
3.0 gallons per minute Discharge Pressure: 145.0 pounds per square inch gage Pumping Element Operating Position: Horizontal Prime Mover Type: Electric motor
3.0 gallons per minute Discharge Pressure: 145.0 pounds per square inch gage Pumping Element Operating Position: Horizontal Prime Mover Type: Electric motor Voltage In Volts:
3.0 gallons per minute Discharge Pressure: 145.0 pounds per square inch gage Pumping Element Operating Position: Horizontal Prime Mover Type: Electric motor Voltage In Volts: 115.0 and 200.0
3.0 gallons per minute Discharge Pressure: 145.0 pounds per square inch gage Pumping Element Operating Position: Horizontal Prime Mover Type: Electric motor Voltage In Volts: 115.0 and 200.0 Phase:
3.0 gallons per minute Discharge Pressure: 145.0 pounds per square inch gage Pumping Element Operating Position: Horizontal Prime Mover Type: Electric motor Voltage In Volts: 115.0 and 200.0 Phase: Three
3.0 gallons per minute Discharge Pressure: 145.0 pounds per square inch gage Pumping Element Operating Position: Horizontal Prime Mover Type: Electric motor Voltage In Volts: 115.0 and 200.0 Phase: Three Frequency In Hertz:
3.0 gallons per minute Discharge Pressure: 145.0 pounds per square inch gage Pumping Element Operating Position: Horizontal Prime Mover Type: Electric motor Voltage In Volts: 115.0 and 200.0 Phase: Three Frequency In Hertz: 400.0
3.0 gallons per minute Discharge Pressure: 145.0 pounds per square inch gage Pumping Element Operating Position: Horizontal Prime Mover Type: Electric motor Voltage In Volts: 115.0 and 200.0 Phase: Three Frequency In Hertz: 400.0 Shelf Life:
3.0 gallons per minute Discharge Pressure: 145.0 pounds per square inch gage Pumping Element Operating Position: Horizontal Prime Mover Type: Electric motor Voltage In Volts: 115.0 and 200.0 Phase: Three Frequency In Hertz: 400.0 Shelf Life: N/a
3.0 gallons per minute Discharge Pressure: 145.0 pounds per square inch gage Pumping Element Operating Position: Horizontal Prime Mover Type: Electric motor Voltage In Volts: 115.0 and 200.0 Phase: Three Frequency In Hertz: 400.0 Shelf Life: N/a

Fiig: A19400