
NSN 4320-00-082-6044

Rotary Pump - Page 1 of 2



Mounting Type:

Frame

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Drive Connection Type:

Rigid coupled

Media For Which Designed:

Hydrocarbon fuels and oils

Maximum Discharge Flow Rate:

4.2 gallons per minute

Discharge Pressure:

1500.0 pounds per square inch gage

Operating Speed At Rated Capacity:

3250.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Pump Rotation Direction:

Clockwise

Rotary Pump Design:

Gear

Operation Method:

Powered

Drive Shaft Type:

Splined, involute external

Drive Shaft End Diameter:

Between 0.4150 inches and 0.5722 inches

Drive Shaft Length:

0.625 inches

Discharge Connection Thread Size And Series/type Designator:

0.250-18 npt

Intake Connection Thread Size And Series/type Designator:

0.375-18 npt

Shelf Life:

N/a

Unit Of Measure:



NSN 4320-00-082-6044

Rotary Pump - Page 2 of 2

Demilitarization:

No

Fiig:

A19400

