

View Online at <https://aerobasegroup.com/nsn/4320-00-085-1081>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Alcohol

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Round flange

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Threaded internal

**Current Type:**

Ac

**Media For Which Designed:**

Alkali solution

**Environmental Protection:**

Watertight

**Pump Quantity:**

1

**Cooling Method:**

Air to air cooled

**Maximum Discharge Flow Rate:**

4.4 gallons per minute

**Discharge Pressure:**

60.0 pounds per square inch gage

**Pumping Element Operating Position:**

Horizontal

**Volume Control Type:**

Rotary

**Control Location:**

Right side

**Rotary Pump Design:**

Lobe

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Current Rating In Amps:**

1.0

**Discharge Connection Thread Size And Series/type Designator:**

0.750-16 unf

**Prime Mover Power Rating:**

0.250 horsepower

**Voltage In Volts:**

200.0

**Phase:**

Three

**Frequency In Hertz:**

400.0

**Reference Number Differentiating Characteristics:**

As differentiated by source control dwg no. 370105

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A19400