

View Online at <https://aerobasegroup.com/nsn/4320-00-085-1081>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Alcohol

Intake Connection Quantity:

1

Intake Connection Type:

Round flange

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Current Type:

Ac

Media For Which Designed:

Alkali solution

Environmental Protection:

Watertight

Pump Quantity:

1

Cooling Method:

Air to air cooled

Maximum Discharge Flow Rate:

4.4 gallons per minute

Discharge Pressure:

60.0 pounds per square inch gage

Pumping Element Operating Position:

Horizontal

Volume Control Type:

Rotary

Control Location:

Right side

Rotary Pump Design:

Lobe

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

1.0

Discharge Connection Thread Size And Series/type Designator:

0.750-16 unf

Prime Mover Power Rating:

0.250 horsepower

Voltage In Volts:

200.0

Phase:

Three

Frequency In Hertz:

400.0

Reference Number Differentiating Characteristics:

As differentiated by source control dwg no. 370105

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400