

View Online at <https://aerobasegroup.com/nsn/4320-00-086-4355>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Base

Stage Quantity:

1

Intake Connection Quantity:

2

Intake Connection Type:

Round flange

Discharge Connection Quantity:

2

Discharge Connection Type:

Round flange

Current Type:

Dc

Media For Which Designed:

Water, salt and water, fresh

Environmental Protection:

Dripproof

Pump Quantity:

2

Cooling Method:

Self ventilated

Maximum Discharge Flow Rate:

160.0 gallons per minute and 110.0 gallons per minute

Discharge Pressure:

35.0 pounds per square inch gage and 45.0 pounds per square inch gage

Operating Speed At Rated Capacity:

3200.0 revolutions per minute and 3200.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Centrifugal Pump Design:

Radial flow

Centrifugal Pump Impeller Quantity:

1

Operation Relationship Design:

Simultaneous

Unpackaged Unit Length:

53.300 inches

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Prime Mover Power Rating:

15.000 horsepower

Voltage In Volts:

500.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400