NSN 4320-00-088-4233

Centrifugal Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-00-088-4233

Prime Mover Quantity:
1
Stage Quantity:
1
Discharge Connection Quantity:
1
Discharge Connection Type:
Threaded internal
Current Type:
Ac
Environmental Protection:
Waterproof
Pump Quantity:
1
Maximum Discharge Flow Rate:
12.0 gallons per minute
Total Head:
30.000 feet
Operating Speed At Rated Capacity:
1800.0 revolutions per minute
Pumping Element Operating Position:
Vertical
Centrifugal Pump Design:
Radial flow
Centrifugal Pump Impeller Quantity:
1
Centrifugal Pump Impeller Suction Type:
Single
Operation Relationship Design:
Simultaneous
Prime Mover Type:
Electric motor
Inclosure Type:
Fully enclosed
Discharge Connection Thread Size And Series/type Designator:
1.250-11-1/2 npt
Prime Mover Power Rating:
0.333 horsepower
Voltage In Volts:
115.0
Phase:
Single

NSN 4320-00-088-4233

Centrifugal Pump Unit - Page 2 of 2



Frequency	In I	-lertz:
-----------	------	---------

60.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400