NSN 4320-00-088-7273

Centrifugal Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-00-088-7273

Prime Mover Quantity:
1
Prime Mover Cooling Medium:
Air
Stage Quantity:
1
Intake Connection Quantity:
1
Intake Connection Type:
Round flange
Discharge Connection Quantity:
1
Discharge Connection Type:
Round flange
Current Type:
Ac
Media For Which Designed:
Water, fresh
Environmental Protection:
Watertight
Pump Quantity:
1
Cooling Method:
Self ventilated
Maximum Discharge Flow Rate:
25.0 gallons per minute
Discharge Pressure:
34.5 pounds per square inch gage
Total Head:
80.000 feet
Operating Speed At Rated Capacity:
3500.0 revolutions per minute
Pumping Element Operating Position:
Vertical
Centrifugal Pump Design:
Radial flow
Centrifugal Pump Impeller Quantity:
1
Centrifugal Pump Impeller Suction Type:
Single
Prime Mover Type:
Electric motor

NSN 4320-00-088-7273

Centrifugal Pump Unit - Page 2 of 2



Inclosure Type:
Partially enclosed
Current Rating In Amps:
3.3
Voltage In Volts:
440.0
Phase:
Three
Frequency In Hertz:
60.0
Specification Or Standard:
D-1 class
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A19400