

View Online at <https://aerobasegroup.com/nsn/4320-00-088-9398>

**Mounting Type:**

Skid

**Discharge Connection Flange Thickness:**

1.000 inches

**Prime Mover Type:**

Diesel engine

**Discharge Connection Type:**

Flanged

**Capacity Rating:**

600.0 gallons per minute

**Suction Connection Type:**

Flanged

**Pump Type:**

Centrifugal

**Suction Connection Flange Type:**

Drilled

**Suction Connection Flange Thickness:**

1.000 inches

**Suction Connection Flange Bolt Circle Diameter:**

9.500 inches

**Suction Connection Flange Bolt Hole Quantity:**

8

**Suction Connection Flange Bolt Hole Diameter:**

0.812 inches

**Discharge Connection Flange Bolt Circle Diameter:**

9.500 inches

**Discharge Connection Flange Bolt Hole Quantity:**

8

**Discharge Connection Flange Bolt Hole Diameter:**

0.812 inches

**Explosion Proof Feature:**

Not included

**Discharge Connection Flange Type:**

Drilled

**Hose Type:**

Suction

**Hose Section Quantity:**

4

**Hose Length:**

20.000 feet

**Hose Inside Diameter:**

6.000 inches

**Ground Cable:**

Included

**Cable Reel:**

Not included

**Drum Emptying Manifold Assembly:**

Not included

**Specification Or Standard:**

2 class

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

T103-m