

View Online at <https://aerobasegroup.com/nsn/4320-00-089-0557>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Base

Intake Connection Quantity:

1

Intake Connection Type:

Threaded internal

Discharge Connection Quantity:

1

Discharge Connection Type:

Threaded internal

Current Type:

Ac

Media For Which Designed:

Hydrocarbon fuels and oils

Environmental Protection:

Drip-proof

Pump Quantity:

1

Maximum Discharge Flow Rate:

1.7 gallons per minute

Discharge Pressure:

50.0 pounds per square inch gage

Operating Speed At Rated Capacity:

11300.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Rotary Pump Design:

Gear

Prime Mover Type:

Electric motor

Inclosure Type:

Partially enclosed

Discharge Connection Thread Size And Series/type Designator:

0.562-18 unf

Intake Connection Thread Size And Series/type Designator:

0.562-18 unf

Prime Mover Power Rating:

0.180 horsepower

Voltage In Volts:

115.0 and 200.0

Phase:

Three

Special Features:

Relief valve set at 180 psi

Frequency In Hertz:

400.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A19400