NSN 4320-00-089-1525

Rotary Pump Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-00-089-1525

Prime Mover Quantity:
1
Prime Mover Cooling Medium:
Air
Mounting Type:
Base
Intake Connection Quantity:
1
Intake Connection Type:
Round flange
Discharge Connection Quantity:
1
Discharge Connection Type:
Round flange
Current Type:
Ac
Media For Which Designed:
Oil
Environmental Protection:
Splashtight
Pump Quantity:
1
Cooling Method:
Self ventilated
Maximum Discharge Flow Rate:
Maximum Discharge Flow Nate.
10.0 gallons per minute
_
10.0 gallons per minute
10.0 gallons per minute Discharge Pressure:
10.0 gallons per minute Discharge Pressure: 50.0 pounds per square inch gage
10.0 gallons per minute Discharge Pressure: 50.0 pounds per square inch gage Operating Speed At Rated Capacity:
10.0 gallons per minute Discharge Pressure: 50.0 pounds per square inch gage Operating Speed At Rated Capacity: 350.0 revolutions per minute
10.0 gallons per minute Discharge Pressure: 50.0 pounds per square inch gage Operating Speed At Rated Capacity: 350.0 revolutions per minute Pumping Element Operating Position:
10.0 gallons per minute Discharge Pressure: 50.0 pounds per square inch gage Operating Speed At Rated Capacity: 350.0 revolutions per minute Pumping Element Operating Position: Horizontal
10.0 gallons per minute Discharge Pressure: 50.0 pounds per square inch gage Operating Speed At Rated Capacity: 350.0 revolutions per minute Pumping Element Operating Position: Horizontal Rotary Pump Design:
10.0 gallons per minute Discharge Pressure: 50.0 pounds per square inch gage Operating Speed At Rated Capacity: 350.0 revolutions per minute Pumping Element Operating Position: Horizontal Rotary Pump Design: Vane
10.0 gallons per minute Discharge Pressure: 50.0 pounds per square inch gage Operating Speed At Rated Capacity: 350.0 revolutions per minute Pumping Element Operating Position: Horizontal Rotary Pump Design: Vane Prime Mover Type:
10.0 gallons per minute Discharge Pressure: 50.0 pounds per square inch gage Operating Speed At Rated Capacity: 350.0 revolutions per minute Pumping Element Operating Position: Horizontal Rotary Pump Design: Vane Prime Mover Type: Electric motor
10.0 gallons per minute Discharge Pressure: 50.0 pounds per square inch gage Operating Speed At Rated Capacity: 350.0 revolutions per minute Pumping Element Operating Position: Horizontal Rotary Pump Design: Vane Prime Mover Type: Electric motor Inclosure Type:
10.0 gallons per minute Discharge Pressure: 50.0 pounds per square inch gage Operating Speed At Rated Capacity: 350.0 revolutions per minute Pumping Element Operating Position: Horizontal Rotary Pump Design: Vane Prime Mover Type: Electric motor Inclosure Type: Fully enclosed
10.0 gallons per minute Discharge Pressure: 50.0 pounds per square inch gage Operating Speed At Rated Capacity: 350.0 revolutions per minute Pumping Element Operating Position: Horizontal Rotary Pump Design: Vane Prime Mover Type: Electric motor Inclosure Type: Fully enclosed Current Rating In Amps:

NSN 4320-00-089-1525

Rotary Pump Unit - Page 2 of 2



Voltage In Volts:
440.0
Phase:
Three
Frequency In Hertz:
60.0
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A19400