

View Online at <https://aerobasegroup.com/nsn/4320-00-097-1359>

**Intake Connection Quantity:**

2

**Intake Connection Type:**

Threaded internal

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Threaded internal

**Drive Connection Type:**

Spur gear

**Media For Which Designed:**

Hydrocarbon fuels and oils

**Maximum Discharge Flow Rate:**

6.6 gallons per minute

**Discharge Pressure:**

55.0 pounds per square inch gage

**Operating Speed At Rated Capacity:**

6540.0 revolutions per minute

**Pump Rotation Direction:**

Clockwise

**Volume Control Type:**

Rotary

**Control Location:**

Center

**Rotary Pump Design:**

Vane

**Operation Method:**

Powered

**Drive Shaft Type:**

Splined, involute external

**Drive Shaft Length:**

0.695 inches

**Discharge Connection Thread Size And Series/type Designator:**

0.562-18 unf

**Intake Connection Thread Size And Series/type Designator:**

0.750-16 unf and 0.750-16 unf

**Reference Number Differentiating Characteristics:**

As differentiated by source control dwg no.4018t11p02 fscm 99207

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A19400