NSN 4320-00-104-2308

Hydraulic Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-00-104-2308

Thread Direction:

Right-hand

Torque Load Rating:

1830.0 inch-pounds

Mounting Type:

Flange

Keyway Width:

0.250 inches

Keyway Depth:

0.125 inches

Mounting Hole Diameter:

0.562 inches

Mounting Hole Quantity:

4

Thread Size:

1.000-11-1/2

Shaft Diameter:

1.094 inches

Operating Speed At Rated Capacity In Rpm:

1800.0

Mounting Bolt Circle Diameter:

5.000 inches

Keyway Length:

2.000 inches

Shaft Thread Size:

1.000-14

Drive Shaft Type:

Machine keyway and threaded

Housing Material:

Iron

Screw Thread Series Designator:

Npt

Shaft Thread Direction:

Right-hand

Shaft Screw Thread Length:

0.812 inches

Shaft Rotation Direction:

Clockwise and counterclockwise

Thread Location:

Internal

Shaft Protrusion Length:

3.875 inches

NSN 4320-00-104-2308

Hydraulic Motor - Page 2 of 2



Connection Quantity:	
1 and 1	

Connection Type:

Outlet

Maximum Working Pressure Rating At Specificationified Tempurature Range:

2000psi at 120 degrees f

Connection Design:

Threaded

Displacement Type:

Constant

Constant Displacement Per Revolution:

7.438 cubic inches

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T103-f