

View Online at <https://aerobasegroup.com/nsn/4320-00-109-5494>

**Prime Mover Quantity:**

1

**Environmental Protection:**

Watertight

**Pump Quantity:**

1

**Maximum Discharge Flow Rate:**

150.0 gallons per minute

**Centrifugal Pump Design:**

Axial flow

**Centrifugal Pump Impeller Quantity:**

1

**Centrifugal Pump Impeller Suction Type:**

Single

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Features Provided:**

Self-priming

**Criticality Code Justification:**

Feat

**Voltage In Volts:**

440.0

**Special Features:**

Items are being coded as critical to insure source inspection will be performed at the point of manufacture, prior to material receipt by the us navy or other dod components. These items are piece parts or end items in support of vital military hardware necessary to sustain the successful mission of the ships, submarines, and shore stations of the us navy. Critical features including, but not limited to, dimensions, tolerances/clearances, electronic characteristics, and metallurgical properties will bespecified for government q ar (quality assurance representatives) to insure the highest possible degree of quality and reliability of these parts being delivered under navicp contracts

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A19400