## NSN 4320-00-115-0178

Hydraulic Motor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4320-00-115-0178

Thread Direction:
Right-hand
Torque Load Rating:
1930.0 inch-pounds
Mounting Type:
Flange
Mounting Hole Diameter:
0.375 inches
Mounting Hole Quantity:
4
Thread Size:
0.500-14
Shaft Diameter:
1.000 inches
Operating Speed At Rated Capacity In Rpm:
137.0
Mounting Bolt Circle Diameter:
3.250 inches
Drive Shaft Type:
Woodruff keyway
Housing Material:
Steel
Screw Thread Series Designator:
Npt
Shaft Rotation Direction:
Clockwise and counterclockwise
Distance From End To Keyway Center:
Distance From End To Keyway Center: 0.730 inches
0.730 inches
0.730 inches Thread Location:
0.730 inches  Thread Location: Internal
0.730 inches  Thread Location: Internal  Shaft Protrusion Length:
0.730 inches  Thread Location: Internal  Shaft Protrusion Length: 1.660 inches
0.730 inches  Thread Location: Internal  Shaft Protrusion Length: 1.660 inches  Connection Quantity:
0.730 inches  Thread Location: Internal  Shaft Protrusion Length: 1.660 inches  Connection Quantity: 1 and 1
0.730 inches Thread Location: Internal Shaft Protrusion Length: 1.660 inches Connection Quantity: 1 and 1 Connection Type:
0.730 inches Thread Location: Internal Shaft Protrusion Length: 1.660 inches Connection Quantity: 1 and 1 Connection Type: Outlet
0.730 inches Thread Location: Internal Shaft Protrusion Length: 1.660 inches Connection Quantity: 1 and 1 Connection Type: Outlet Maximum Working Pressure Rating At Specificationified Tempurature Range:
0.730 inches Thread Location: Internal Shaft Protrusion Length: 1.660 inches Connection Quantity: 1 and 1 Connection Type: Outlet Maximum Working Pressure Rating At Specificationified Tempurature Range: 800psi at 180 degrees f

15

## **NSN 4320-00-115-0178** Hydraulic Motor - Page 2 of 2



Fiig: T103-f