

View Online at <https://aerobasegroup.com/nsn/4320-00-115-5078>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Mounting Type:

Base

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Round flange

Discharge Connection Quantity:

1

Discharge Connection Type:

Round flange

Current Type:

Dc

Media For Which Designed:

Water, salt

Environmental Protection:

Dripproof

Pump Quantity:

1

Cooling Method:

Blower cooled

Maximum Discharge Flow Rate:

250.0 gallons per minute

Total Head:

231.000 feet

Operating Speed At Rated Capacity:

3500.0 revolutions per minute

Pumping Element Operating Position:

Horizontal

Centrifugal Pump Design:

Radial flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Double

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

110.0

Features Provided:

Self-priming

Voltage In Volts:

230.0

Specification Or Standard:

C2 class

Reference Number Differentiating Characteristics:

As differentiated by w/reliance electric motor, dwg no. 87920

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A19400