

View Online at <https://aerobasegroup.com/nsn/4320-00-115-5086>

**Prime Mover Quantity:**

1

**Prime Mover Cooling Medium:**

Air

**Mounting Type:**

Base

**Stage Quantity:**

2

**Intake Connection Quantity:**

1

**Intake Connection Type:**

Round flange

**Discharge Connection Quantity:**

1

**Discharge Connection Type:**

Round flange

**Current Type:**

Dc

**Media For Which Designed:**

Water, salt

**Pump Quantity:**

1

**Cooling Method:**

Blower cooled

**Maximum Discharge Flow Rate:**

400.0 gallons per minute

**Total Head:**

289.000 feet

**Operating Speed At Rated Capacity:**

1750.0 revolutions per minute

**Pumping Element Operating Position:**

Horizontal

**Centrifugal Pump Design:**

Radial flow

**Centrifugal Pump Impeller Quantity:**

2

**Centrifugal Pump Impeller Suction Type:**

Single

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Current Rating In Amps:**

175.0

**Features Provided:**

Self-priming

**Prime Mover Power Rating:**

50.000 horsepower

**Voltage In Volts:**

230.0

**Specification Or Standard:**

C2 class

**Reference Number Differentiating Characteristics:**

As differentiated by w/reliance electric motor, dwg no. 87575

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A19400