

View Online at <https://aerobasegroup.com/nsn/4320-00-116-3633>

Prime Mover Quantity:

1

Prime Mover Cooling Medium:

Air

Stage Quantity:

1

Intake Connection Quantity:

1

Intake Connection Type:

Round flange

Discharge Connection Quantity:

1

Discharge Connection Type:

Round flange

Current Type:

Ac

Pump Quantity:

1

Cooling Method:

Blower cooled

Maximum Discharge Flow Rate:

18.0 gallons per minute

Discharge Pressure:

26.0 pounds per square inch gage

Operating Speed At Rated Capacity:

3500.0 revolutions per minute

Pumping Element Operating Position:

Vertical

Centrifugal Pump Design:

Radial flow

Centrifugal Pump Impeller Quantity:

1

Centrifugal Pump Impeller Suction Type:

Single

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Current Rating In Amps:

3.1

Features Provided:

Self-priming

Prime Mover Power Rating:

2.000 horsepower

Voltage In Volts:

440.0

Phase:

Three

Frequency In Hertz:

60.0

Reference Number Differentiating Characteristics:

As differentiated by w/electro dynamic motor, dwg no. 1224-3

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A19400